

INDUSTRIAL COMPONENT DATA

EASY618-DC-RE 232112 4520993 EATON ELECTRIC I/O expansion, 24 V DC, 12DI, 6DO relays, easyLink

Brand: EATON - MOELLER | Manufacturer Part Number: EASY618-DC-RE



Manufacturer	EATON - MOELLER
MPN / Reference	EASY618-DC-RE
Catalog number	4520993
Category	Logic module
Minimum order	1 Pcs
Document ID	EO-CBE8DC2D07
Generated	2026-08-05

Product Overview

I/O expansion, 24 V DC, 12DI, 6DO relays, easyLink

Easy Extension Module; 24 V DC; 12 ED, 6 SR

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER
--------------	-----------------

Additional Product Information

EL-Nummer (Norway)4520993I/O expansion, 24 V DC, 12DI, 6DO relays, easyLinkI/O expansion, rated operating voltage 24VDC, 12 digital inputs 24VDC, 6 relay outputs, can be used via easyLink for easy700, easy800, MFD-CP8/CP10, EC4P, EC4E, ES4PDelivery program

Product rangeControl relay easyRelay

Multi-function-display MFD-TitanProduct rangeRemote I/O systems

Compact PLCsSubrangeI/O expansions digitalBasic functionExpansionsDescriptionCan be used through easyLinkFunctionExpansions EASY...AccessoriesI/O expansions, digitalInputsInputs expansion (number)digital: 12Supply voltage24 V DCFor use witheasy700

easy800

EC4P

MFD-CP8..Technical data

GeneralWeight0.3 kgClimatic environmental conditionsOperating ambient temperature-25 to + 55

cold as per IEC 60068-2-1

heat as per IEC 60068-2-2 °CCondensationTake appropriate measures to prevent condensationStorage [?]-40 - +70

°C relative humidity 5 - 95 % Air pressure (operation) 795 - 1080 hPa Ambient conditions, mechanical Protection type (IEC/EN 60529, EN50178, VBG 4) IP20 Vibrations (IEC/EN 60068-2-6) Constant amplitude 0.15 mm 10 - 57 Hz Vibrations (IEC/EN 60068-2-6) Constant acceleration 2 g 57 - 150 Hz Mechanical shock resistance (IEC/EN 60068-2-27) semi-sinusoidal 15 g/11 ms 18 Impacts Drop to IEC/EN 60068-2-31 [Drop height] 50 mm Free fall, packaged (IEC/EN 60068-2-32) 1 m Mounting position Vertical or horizontal Electromagnetic compatibility (EMC) Overvoltage category/pollution degree II/2 Electrostatic discharge (ESD) applied standard IEC/EN 61000-4-2, Level....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / EASY618-DC-RE with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.