

INDUSTRIAL COMPONENT DATA

EASY620-DC-TE 212313 0004520946 EATON ELECTRIC I/O expansion, 24 V DC, 12DI, 8DO-Trans, easyLink

Brand: EATON - MOELLER | Manufacturer Part Number: EASY620-DC-TE



Manufacturer	EATON - MOELLER
MPN / Reference	EASY620-DC-TE
Catalog number	0004520946
Category	Logic module
Minimum order	1 Pcs
Document ID	EO-1860036BA1
Generated	2026-08-06

Product Overview

I/O expansion, 24 V DC, 12DI, 8DO-Trans, easyLink

Easy Extension Module; 24 V DC; 12 ED, 8 SD

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > EASY programmable relays and MFD displays

Additional Product Information

EL-Nummer (Norway)4520946I/O expansion, 24 V DC, 12DI, 8DO-Trans, easyLinkI/O expansion, rated operating voltage 24VDC, 12 digital inputs 24VDC, 8 transistor outputs 24VDC, can be used via easyLink for easy700, easy800, MFD-CP8/CP10, EC4P, EC4E, ES4PDelivery program

Product rangeControl relay easyRelay

Multi-function-display MFD-TitanProduct rangeRemote I/O systems

Compact PLCsSubrangeI/O expansions digitalBasic functionExpansionsDescriptionCan be used through easyLinkFunctionExpansions EASY...AccessoriesI/O expansions, digitalInputsInputs expansion (number)digital:

12OutputsTransistor8Supply voltage24 V DCFor use witheasy700

easy800

EC4P

MFD-CP8..Technical data

GeneralWeight0.3 kgClimatic environmental conditionsOperating ambient temperature-25 to + 55

cold as per IEC 60068-2-1

heat as per IEC 60068-2-2 °CCondensationTake appropriate measures to prevent condensationStorage [?]-40 - +70

°Crelative humidity5 - 95 %Air pressure (operation)795 - 1080 hPaAmbient conditions, mechanicalProtection type (IEC/EN 60529, EN50178, VBG 4)IP20Vibrations (IEC/EN 60068-2-6)Constant amplitude 0.15 mm10 - 57 HzVibrations (IEC/EN 60068-2-6)Constant acceleration 2 g57 - 150 HzMechanical shock resistance (IEC/EN 60068-2-27) semi-sinusoidal 15 g/11 ms18 ImpactsDrop to IEC/EN 60068-2-31 [Drop height]50 mmFree fall, packaged (IEC/EN 60068-2-32)1 mMounting positionVertical or horizontalElectromagnetic compatibility (EMC)Overvoltage category/pollution degreeII/2Electrostatic discharge (ESD)applied stan...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / EASY620-DC-TE with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.