

INDUSTRIAL COMPONENT DATA

EASY411-DC-ME 116567 0004560807 EATON ELECTRIC I/O expansion, 24 V DC, 1DI, 6AI-2x(Pt100, V, mA), 2DO, 2AO, ..

Brand: EATON - MOELLER | Manufacturer Part Number: EASY411-DC-ME



Manufacturer	EATON - MOELLER
MPN / Reference	EASY411-DC-ME
Catalog number	0004560807
Category	Logic module
Minimum order	1 Pcs
Document ID	EO-E07B63FC6D
Generated	2026-08-06

Product Overview

I/O expansion, 24 V DC, 1DI, 6AI-2x(Pt100, V, mA), 2DO, 2AO, easyLink

Easy Extension Module; 24 V DC; 1 ED, 6 EA, 2x(Pt100,V,mA), 2 SD, 2 SA

Control relay expansion, rated operating voltage 24VDC, 1 digital input 24VDC, 6 analog inputs selectively usable as voltage (2x0-10 V), current (2x0-20 mA), or temperature inputs (2xPt100) or arbitrarily combined, 2 transistor outputs, 2 analog outputs(0-10V), can be used via easyLink for easy800, MFD-CP8/CP10, EC4P, EC4E, ES4P

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > EASY programmable relays and MFD displays

Additional Product Information

I/O expansion, 24 V DC, 1DI, 6AI-2x(Pt100, V, mA), 2DO, 2AO, easyLink Control relay expansion, rated operating voltage 24VDC, 1 digital input 24VDC, 6 analog inputs selectively usable as voltage (2x0-10 V), current (2x0-20 mA), or temperature inputs (2xPt100) or arbitrarily combined, 2 transistor outputs, 2 analog outputs(0-10V), can be used via easyLink for easy800, MFD-CP8/CP10, EC4P, EC4E, ES4P Delivery program

Product range Control relay easyRelay

Multi-function-display MFD-Titan Product range Remote I/O systems

Compact PLCs Subrange I/O expansions analog Basic function Expansions Description Can be used through easyLink

Function Expansions EASY... Accessories I/O expansions, analog Inputs Inputs expansion (number) digital: 1; analog: 6 (0-10V:2 and 0-20mA:2 and Pt100:2) Analog 6 Outputs Transistor 2 Supply voltage 24 V DC For use with easy800

EC4P

MFD-CP8...

MFD-CP10... Technical data

General Dimensions (W x H x D) 71.5 x 90 x 58 (4 PE) mm Weight 0.2 kg Climatic environmental conditions Operating ambient temperature -25 to + 55

cold as per IEC 60068-2-1

heat as per IEC 60068-2-2 °C Condensation Take appropriate measures to prevent condensation Storage [?] -40 - +70 °C relative humidity 5 - 95 % Air pressure (operation) 795 - 1080 hPa Ambient conditions, mechanical Protection type (IEC/EN 60529, EN50178, VBG 4) IP20 Vibrations (IEC/EN 60068-2-6)Constant amplitude 0.15 mm 10 - 57 Hz Vibrations (IEC/EN 60068-2-6)Constant acceleration 2 g 57 - 150 Hz Mechanical shock resistance...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / EASY411-DC-ME with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.