

INDUSTRIAL COMPONENT DATA

EASY202-RE 232186 0004520992 EATON ELECTRIC I/O expansion, 24 V DC, 2DO relays, easyLink

Brand: EATON - MOELLER | Manufacturer Part Number: EASY202-RE



Manufacturer	EATON - MOELLER
MPN / Reference	EASY202-RE
Catalog number	0004520992
Category	Logic module
Minimum order	1 Pcs
Document ID	EO-BA77129620
Generated	2026-08-06

Product Overview

I/O expansion, 24 V DC, 2DO relays, easyLink

Easy Extension Module; 2 Relay Outputs

Control relay expansion, rated operating voltage 24VDC, 2 relay outputs (common potential), can be used through easyLink cannot be used in combination with basic device EASY719-DA..., cannot be used with coupling module EASY200-easy

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > EASY programmable relays and MFD displays
--------------	---

Additional Product Information

I/O expansion, 24 V DC, 2DO relays, easyLink Control relay expansion, rated operating voltage 24VDC, 2 relay outputs (common potential), can be used through easyLink cannot be used in combination with basic device EASY719-DA..., cannot be used with coupling module EASY200-easy Delivery program

Product range Control relay easyRelay

Multi-function-display MFD-Titan Product range Remote I/O systems

Compact PLCs Subrange I/O expansions digital Basic function Expansions Description Can be used through easyLink

Function Expansions EASY... Accessories I/O expansions, digital Supply voltage 24 V DC For use with easy700 easy800

EC4P

MFD-CP8... Technical data

General Dimensions (W x H x D) 35.5 x 90 x 58 (2 PE) mm Weight 0.07 kg Terminal capacities Solid 0.2/4 (AWG 22 - 12) mm2 Climatic environmental conditions Storage [?] -40 - +70 °C Electromagnetic compatibility (EMC) Overvoltage

category/pollution degree II/2 Electrostatic discharge (ESD) applied standard IEC EN 61000-4-2, Level 3 power pulses (Surge) 2 kV (supply cables, symmetrical, EASY...AC)
0.5 kV (supply cables, symmetrical, easy-DC)
according to IEC/EN 61000-4-5 Power supply Rated operational voltage [Ue] 24 DC (-15/+20%) V Relay outputs Number 2
Outputs in groups of 2 Parallel switching of outputs for increased output Not permissible Protection of an output relay
Miniature circuit-breaker B16 or fuse 8 A (slow) Potential isolation from power supply: yes
From the inputs: yes
Safe isolation according to EN 50178: 300 V AC
Basic i...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / EASY202-RE with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.