

INDUSTRIAL COMPONENT DATA

EASY410-DC-TE 114294 0004560803 EATON ELECTRIC I/O expansion, 24 V DC, 6DI, 4DO-Trans, easyLink

Brand: EATON - MOELLER | Manufacturer Part Number: EASY410-DC-TE



Manufacturer	EATON - MOELLER
MPN / Reference	EASY410-DC-TE
Catalog number	0004560803
Category	Logic module
Minimum order	1 Pcs
Document ID	EO-6E9CD58759
Generated	2026-08-05

Product Overview

I/O expansion, 24 V DC, 6DI, 4DO-Trans, easyLink

Easy Extension Module; 24 V DC; 6 ED, 4 SD

Control relay expansion, rated operating voltage 24VDC, 6 digital inputs 24VDC, 4 transistor outputs, can be used via easyLink for easy700, easy800, MFD-CP8/CP10, EC4P, EC4E, ES4P

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > EASY programmable relays and MFD displays
--------------	---

Additional Product Information

I/O expansion, 24 V DC, 6DI, 4DO-Trans, easyLink Control relay expansion, rated operating voltage 24VDC, 6 digital inputs 24VDC, 4 transistor outputs, can be used via easyLink for easy700, easy800, MFD-CP8/CP10, EC4P, EC4E, ES4P

Delivery program

Product range Control relay easyRelay

Multi-function-display MFD-Titan Product range Remote I/O systems

Compact PLCs Subrange I/O expansions digital Basic function Expansions Description Can be used through easyLink

Function Expansions EASY... Accessories I/O expansions, digital Inputs Inputs expansion (number) digital: 6 Outputs

Transistor 4 Supply voltage 24 V DC For use with easy700

easy800

EC4P

MFD-CP8...

MFD-CP10... Technical data

General Dimensions (W x H x D) 71.5 x 90 x 58 (4 PE) mm Weight 0.2 kg Climatic environmental conditions Operating ambient temperature -25 to + 55

cold as per IEC 60068-2-1

heat as per IEC 60068-2-2 °C Condensation Take appropriate measures to prevent condensation Storage [?] -40 - +70 °C relative humidity 5 - 95 % Air pressure (operation) 795 - 1080 hPa Ambient conditions, mechanical Protection type (IEC/EN 60529, EN50178, VBG 4) IP20 Vibrations (IEC/EN 60068-2-6)Constant amplitude 0.15 mm 10 - 57 Hz Vibrations (IEC/EN 60068-2-6)Constant acceleration 2 g 57 - 150 Hz Mechanical shock resistance (IEC/EN 60068-2-27) semi-sinusoidal 15 g/11 ms 18 Impacts Drop to IEC/EN 60068-2-31 [Drop height] 50 mm Free fall, packaged (IEC/EN 60068-2-32) 1 m Mounting position Vertical or horizontal Electromagnetic compatibili...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / EASY410-DC-TE with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.