

INDUSTRIAL COMPONENT DATA

EC4E-221-6D4T1 114297 4560854 EATON ELECTRIC I/O expansion, integrated, 24 V DC, 6DI, 4DO(T)

Brand: EATON - MOELLER | Manufacturer Part Number: EC4E-221-6D4T1



Manufacturer	EATON - MOELLER
MPN / Reference	EC4E-221-6D4T1
Catalog number	4560854
Category	PLC digital I/O-module
Minimum order	1 Pcs
Document ID	EO-C7EF169C4A
Generated	2026-08-05

Product Overview

I/O expansion, integrated, 24 V DC, 6DI, 4DO(T)

EC4E-221-6D4T1

I/O expansion via CANopen. Can be used for XC100/200, EC4P, XV-...

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog pathEATON - MOELLER > EC4P PLCs

Additional Product Information

EL-Nummer (Norway)4560854I/O expansion, integrated, 24 V DC, 6DI, 4DO(T)I/O expansion via CANopen. Can be used for XC100/200, EC4P, XV-...Delivery program

Product rangeRemote I/O systems

Compact PLCsSubrangeI/O expansions digital/analogBasic functionExpansionsDescriptionusable via

CANopen®FunctionCANopen® expansion EC4EInputsInputs expansion (number)Digital: 6OutputsTransistor4Additional featuresReal time clock?Supply voltage24 V DCFor use witheasy800

EC4P

MFD-CP8...

MFD-CP10...For use withXC100/200, EC4P, MFD4 (via CANopen®)Technical data

GeneralDimensions (W x H x D)71.5 x 90 x 58 (4 PE) mmWeight0.2 kgMountingTop-hat rail IEC/EN 60715, 35 mm or screw fixing using fixing brackets ZB4-101-GF1 (accessories)Terminal capacitiesSolid0.2/4 (AWG 22 - 12) mm2Flexible with ferrule0.2/2.5 (AWG 22 - 12) mm2Standard screwdriver0.8 x 3.5 mmMax. tightening torque0.6 NmClimatic environmental conditionsOperating ambient temperature-25 to 55, cold as per IEC 60068-2-1, heat as per IEC 60068-2-2

°CCondensationTake appropriate measures to prevent condensationStorage [?]-40 - +70 °CAmbient conditions,
mechanicalMounting positionVertical or horizontalElectromagnetic compatibility (EMC)Overvoltage category/pollution
degreeII/2Electrostatic discharge (ESD)applied standardIEC/EN 61000-4-2, Level 3Electrostatic discharge (ESD)Air
discharge8 kVElectromagnetic fields (RFI) to IEC EN 61000-4-310 V/mBurstaccording to IEC/EN 61000-4-4 kVpower
pulses (Surge)2 kV (supply cables, symmetrical, EASY...AC)
0.5 kV...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / EC4E-221-6D4T1 with the required quantity to info@electricaonline.com or use
electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd
Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification
requirements against the manufacturer documentation before purchase or installation.