

INDUSTRIAL COMPONENT DATA

i-P65, 3h, open area Autotest IP65LEDO3HIS EATON ELECTRIC i-P65, 3h, open area Test

Brand: EATON - MOELLER | Manufacturer Part Number: i-P65, 3h, open area Autotest



Manufacturer	EATON - MOELLER
MPN / Reference	i-P65, 3h, open area Autotest
Catalog number	IP65LEDO3HIS
Category	Emergency luminaire
Minimum order	1 Pcs
Document ID	EO-F7EADE26CA
Generated	2026-08-06

Product Overview

i-P65, 3h, open area Test

Eaton i-P65, Safety lighting, 20m viewing distance, Open area, Auto-Test, LED, Maintained / Non-Maintained operation, IP65, 153lm, 3 hour duration

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Self contained
--------------	----------------------------------

Additional Product Information

ETIM for IP65LEDO3HIS Luminaires (EC001957)

Feature Name

Feature Value

Suitable for labelling type (EF001277)

Sticker

With pictogram (EF011099)

No

Monitoring equipment (EF008091)

Automatic self test

With remote switch connection (EF007947)

Yes

Power supply system (EF000233)

Peripheral (individual battery)

Battery technology (EF004351)

NiCd

Lamp type (EF002423)

LED non-replaceable

With light source (EF005905)

Yes

Lamp holder (EF000048)

None

Number of lighting heads (EF004258)

1

Housing material (EF001596)

Plastic

Housing colour (EF000136)

Grey

Material cover (EF004284)

Plastic transparent

Voltage type (EF000187)

AC

Nominal voltage (EF005127)

220 V

Type of control gear (EF000381)

LED driver constant current

Light distributor (EF012170)

Focal lens

Degree of protection (IP) (EF005474)

IP65

Impact strength (EF004293)

IK10

Protection class according to IEC 61140 (EF000004)

I

Luminaire with limited surface temperature, sign "D" according to EN 60598-2-24 (EF006420)

Yes

Rated ambient temperature according to IEC 62722-2-1 (EF012090)

5 °C

Max. system power (EF009347)

2.5 W

Rated luminous flux according to IEC 62722-2-1 (EF009349)

153 lm

Luminous flux in standby mode (EF011954)

153 lm

Colour temperature (EF009346)

6200 K

Power factor (EF025740)

0.5

Recognition distance (EF008732)

20 m

Nominal operation time (EF012518)

3 h

Width (EF000008)

55 mm

Height/depth (EF001456)

142 mm

Length (EF001438)

263 mm

Built-in width (EF000846)

55 mm

Built-in height/depth (EF023518)

55 mm

Built-in length...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / i-P65, 3h, open area Autotest with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.