

INDUSTRIAL COMPONENT DATA

i-P65 LED 3Hr Open IP65LEDO3H EATON ELECTRIC i-P65, 3h, open area

Brand: EATON - MOELLER | Manufacturer Part Number: i-P65 LED 3Hr Open



Manufacturer	EATON - MOELLER
MPN / Reference	i-P65 LED 3Hr Open
Catalog number	IP65LEDO3H
Category	Emergency luminaire
Minimum order	1 Pcs
Document ID	EO-D31ED63387
Generated	2026-08-04

Product Overview

i-P65, 3h, open area

i-P65 LED 3Hr Open

Eaton i-P65, Safety lighting, 20m viewing distance, Open area, Stand alone, LED, Maintained / Non-Maintained operation, IP65, 153lm, 3 hour duration

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Self contained

Additional Product Information

ETIM for IP65LEDO3H Luminaires (EC001957)

Feature Name

Feature Value

Suitable for labelling type (EF001277)

Sticker

With pictogram (EF011099)

No

Monitoring equipment (EF008091)

None

With remote switch connection (EF007947)

Yes

Power supply system (EF000233)

Peripheral (individual battery)
Battery technology (EF004351)
NiCd
Lamp type (EF002423)
LED non-replaceable
With light source (EF005905)
Yes
Lamp holder (EF000048)
None
Number of lighting heads (EF004258)
1
Housing material (EF001596)
Plastic
Housing colour (EF000136)
Grey
Material cover (EF004284)
Plastic transparent
Voltage type (EF000187)
AC
Nominal voltage (EF005127)
220 V
Type of control gear (EF000381)
LED driver constant current
Light distributor (EF012170)
Focal lens
Degree of protection (IP) (EF005474)
IP65
Impact strength (EF004293)
IK10
Protection class according to IEC 61140 (EF000004)
I
Luminaire with limited surface temperature, sign "D" according to EN 60598-2-24 (EF006420)
Yes
Rated ambient temperature according to IEC 62722-2-1 (EF012090)
5 °C
Max. system power (EF009347)
2.5 W
Rated luminous flux according to IEC 62722-2-1 (EF009349)
153 lm
Luminous flux in standby mode (EF011954)
153 lm
Colour temperature (EF009346)
6200 K
Power factor (EF025740)
0.5
Recognition distance (EF008732)
20 m

Nominal operation time (EF012518)

3 h

Width (EF000008)

55 mm

Height/depth (EF001456)

142 mm

Length (EF001438)

263 mm

Built-in width (EF000846)

55 mm

Built-in height/depth (EF023518)

55 mm

Built-in length (EF004265)

263 m...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / i-P65 LED 3Hr Open with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.