

INDUSTRIAL COMPONENT DATA

i-P65 Plus H 3H CGLine+ PC IP65PHP3HCGL EATON

ELECTRIC i-P65 Plus H 3H CGLine+, PC

Brand: EATON - MOELLER | Manufacturer Part Number: i-P65 Plus H 3H CGLine+ PC



Manufacturer	EATON - MOELLER
MPN / Reference	i-P65 Plus H 3H CGLine+ PC
Catalog number	IP65PHP3HCGL
Category	Emergency luminaire
Minimum order	1 Pcs
Document ID	EO-439B83EB59
Generated	2026-08-04

Product Overview

i-P65 Plus H 3H CGLine+, PC

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Central Battery System

Additional Product Information

General specifications

Product Name Eaton i-P65 Plus SC Emergency Luminaire Catalog Number IP65PHP3HCGL Ean 5018987233361 Product Length/Depth 340 mm Product Height 80.5 mm Product Width 167.9 mm Product Weight 1.733 kg Certifications Ec Product Specifications

Battery voltage 4.8 V Battery quality NiCd Glow wire test 850 °C Protection class The Outdoor use compliance True Explosion protected False Degree of protection IP65 Mode Maintained / Non-Maintained (M/NM) Lamp type LED not exchangeable With light source True Lamp holder None, 19 Lamp power 6.5 W Monitoring equipment Safety module for monitoring (central feeded system) Power supply system Peripheral (individual battery) Voltage type Ac Power factor .5 Wiring system Continuous circuit/emergency circuit With remote switch connection True Reserve-polarity protected True Conductor cross section 2.5 Connection type Plug-in connection Max. system power 3.2 W Rated life time L80/B10 at 25 °C 60000 hour Type of control gear LED operating device current-controlled Type of wiring Suitable for through wiring Nominal voltage AC - max 240 V Nominal voltage AC - min 220 V Apparent power at mains operation(50cd) 21.7 VA Effective power at mains operation (50cd) 10.7 W Rated ambient temp acc. IEC62722-2-1 - Min 5 °C Rated ambient temp acc. IEC62722-2-1 - Max 40 °C Nominal operation time - min 3 hour Nominal operation time - max 3 hour Mounting Method Ceiling surface mounting Material housing Plastic Color housing Grey Material cover P...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / i-P65 Plus H 3H CGLine+ PC with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.