

INDUSTRIAL COMPONENT DATA

i-P65 Plus L 3H CGLine+, Alu IP65PLA3HCGL EATON

ELECTRIC i-P65 Plus L 3H CGLine+, Alu

Brand: EATON - MOELLER | Manufacturer Part Number: i-P65 Plus L 3H CGLine+, Alu



Manufacturer	EATON - MOELLER
MPN / Reference	i-P65 Plus L 3H CGLine+, Alu
Catalog number	IP65PLA3HCGL
Category	Emergency luminaire
Minimum order	1 Pcs
Document ID	EO-7BC4DE8EEF
Generated	2026-08-06

Product Overview

i-P65 Plus L 3H CGLine+, Alu

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Self contained
--------------	----------------------------------

Additional Product Information

ETIM for IP65PLA3HCGL Luminaires (EC001957)

Feature Name

Feature Value

Mounting method (EF000003)

Ceiling surface mounting

Suitable for labelling type (EF001277)

Other

With pictogram (EF011099)

No

Monitoring equipment (EF008091)

Safety module for monitoring (central feeded system)

With remote switch connection (EF007947)

Yes

Power supply system (EF000233)

Peripheral (individual battery)

Battery technology (EF004351)

NiCd

Lamp type (EF002423)

LED non-replaceable

With light source (EF005905)

Yes

Lamp holder (EF000048)

None

Number of lighting heads (EF004258)

1

Housing material (EF001596)

Aluminium

Housing colour (EF000136)

Grey

Material cover (EF004284)

Plastic transparent

Voltage type (EF000187)

AC

Nominal voltage (EF005127)

220 V

Type of control gear (EF000381)

LED driver constant current

Light distributor (EF012170)

Focal lens

Degree of protection (IP) (EF005474)

IP65

Impact strength (EF004293)

IK08

Protection class according to IEC 61140 (EF000004)

I

Luminaire with limited surface temperature, sign "D" according to EN 60598-2-24 (EF006420)

Yes

Rated ambient temperature according to IEC 62722-2-1 (EF012090)

5 °C

Max. system power (EF009347)

3.2 W

Rated luminous flux according to IEC 62722-2-1 (EF009349)

510 lm

Colour temperature (EF009346)

6200 K

Power factor (EF025740)

0.5

Nominal operation time (EF012518)

3 h

Width (EF000008)

167.9 mm

Height/depth (EF001456)

80.5 mm

Length (EF001438)

340 mm

Built-in width (EF000846)

80 mm

Built-in height/depth (EF023518)

168 mm

Built-in l...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / i-P65 Plus L 3H CGLine+, Alu with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.