

INDUSTRIAL COMPONENT DATA

IKA-3/36-ST-UV 174192 Y7-174192 EATON ELECTRIC

IKA-3/36-ST-UV IKA industrial distribution board, UV-stable, ..

Brand: EATON - MOELLER | Manufacturer Part Number: IKA-3/36-ST-UV



Manufacturer	EATON - MOELLER
MPN / Reference	IKA-3/36-ST-UV
Catalog number	Y7-174192
Category	Small distribution board
Minimum order	1 Pcs
Document ID	EO-64283A2D86
Generated	2026-08-05

Product Overview

IKA-3/36-ST-UV IKA industrial distribution board, UV-stable, IP65 + clamps

IKA-3/36-ST-UV

Eaton xComfort IKA LV systems Final Distribution Boards. IKA industrial distribution board, UV-stable, IP65 + clamps, 3/36-ST-UV

IKA distribution board for damp locations RAL7035, with neutral and protective conductor terminal, foamed-in-place gasket, applied using CNC, for IP65 degree of protection as per IEC/EN 62208, 36 space units, 3-row, UV-stable acc. DIN EN ISO 4892-2, approved for building service distribution boards in accordance with IEC/EN 61439-3 VDE 0660-600-3, integrated module compensation system designed to accommodate various device widths, metric knockouts with centering point, enclosure completely made of polycarbonates (UV resistant), for installing switching and protective devices, in accordance with dimension standard DIN 43 880 with an installation depth of 70 mm or 85 mm, AC 1000 V, DC 1500 V, RoHS-compliant, consisting of a plastic base with a withdrawable DIN-rail made of galvanized sheet steel, DIN-rail adjustable in height in 2 positions, direct mounting wall mounting holes, finger-proof IP2X neutral and protective conductor terminals, knockout for metric cable entries on top and bottom, side knockouts for connection element for connecting two or more enclosures next to each other, top with 46-mm device opening, transparent door, flush with front, can be fitte...

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Compact Distribution Boxes

Additional Product Information

General specifications

Product Name Eaton xComfort IKA industrial series Catalog Number 174192 Model Code IKA-3/36-ST-UV EAN

4015081706549 Product Length/Depth 145 mm Product Height 586 mm Product Width 310 mm Product Weight 4.11 kg
Compliances RoHS conform Certifications EN 62208
IEC/EN 60670-24 Delivery program
Type Application Indoor (installation site)
Outdoor (installation site)
Color Light gray (RAL 7035)
Gray Technical data - electrical
Voltage rating at AC 415 V AC Frequency rating of contacts 50 Hz Technical data - mechanical
Closure type Other Enclosure material Plastic Width in number of modular spacings 12 Mounting method DIN-rail
Surface mounted (plaster)
Surface mounting Material Polycarbonate (plastic) Degree of protection IP65
IK08 (impact resistance) Number of module space units per row 12 Number of rows 3 Terminal type Screw terminals PE
and N terminal number and cross section N: 12 x (2.5 mm² - 6 mm²) + 12 x (4 mm² - 10 mm²) + 1 x (10 mm² - 25 mm²) + 1 x
(16 mm² - 35 mm²)
PE: 12 x (2.5 mm² - 6 mm²) + 12 x (4 mm² - 10 mm²) + 1 x (10 mm² - 25 mm²) + 1 x (16 mm² - 35 mm²) Built-in depth 70 mm
Built-in height 0 mm Built-in width 0 mm Internal depth 60 mm Cable entry position Metric cable entries on top and bottom,
side, back plate Cover/door color Transparent Cover/door model With notch Cover/door type Door
Single Module rack type Rail frame Protective shrouding material Plastic Temperature-rise verification as per IEC 60890
Heat diss. ambient 35°C delta T:20°...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / IKA-3/36-ST-UV with the required quantity to info@electricaonline.com or use
electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd
Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification
requirements against the manufacturer documentation before purchase or installation.