

INDUSTRIAL COMPONENT DATA

Q25LTR-BL 086739 Y7-86739 EATON ELECTRIC Illuminated pushbutton actuator, blue, maintained

Brand: EATON - MOELLER | Manufacturer Part Number: Q25LTR-BL



Manufacturer	EATON - MOELLER
MPN / Reference	Q25LTR-BL
Catalog number	Y7-86739
Category	Front element for push button
Minimum order	1 Pcs
Document ID	EO-4E1C1DBEC8
Generated	2026-08-01

Product Overview

Illuminated pushbutton actuator, blue, maintained

Flush luminous pushbutton; 16 mm; 25x25 mm; Interlocking; Blue

Eaton Moeller® series RMQ16 Illuminated pushbutton actuator, blue, maintained Q25LTR-BL

Illuminated pushbutton actuator, Product range: RMQ16, Single unit, Design: Flat, maintained, Description: without light elements, With base, W2x4,6d; max. 30 V, 1 W, button plate: Blue, Button plate Blank, Degree of Protection: IP65, Connection to SmartWire-DT: no, Front dimensions: 25 x 25

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Auxiliary Control and Signalling Elements
--------------	---

Additional Product Information

General specifications

Product Name Eaton Moeller® series RMQ16 Illuminated pushbutton actuator Catalog Number 086739 Model Code Q25LTR-BL EAN 4015080867395 Product Length/Depth 59 mm Product Height 25 mm Product Width 25 mm Product Weight 0.011 kg Certifications UL Category Control No.: NKCR

IEC/EN 60947

UL 508

CE

CSA

CSA Class No.: 3211-03

CSA-C22.2 No. 14-05

UL
CSA File No.: 46552
IEC/EN 60947-5
UL File No.: E29184 Catalog Notes Filament bulb or LED needs to be ordered separately Features & Functions
Bezel color Black Bezel material Plastic Design Flat Inscription Blank General
Degree of protection IP65
NEMA 1 Degree of protection (front side) NEMA 1
IP65 Lifespan, mechanical 30,000,000 Operations Opening diameter 16 mm Operating frequency 1800 Operations/h
Overvoltage category III Pollution degree 3 Product category RMQ16 Rated impulse withstand voltage (Uimp) 800 V AC
Size Front dimensions: 25 x 25 mm Suitable for Illumination Terminal capacity 0.5 - 1.0 mm² Terminal size 2.8 x 0.8 mm to
DIN 46244, Blade terminal
2.8 x 0.8 mm to DIN 46247 and IEC 60760, Fast-on connectors Type Illuminated pushbutton actuator Ambient conditions,
mechanical
Mounting position As required Shock resistance Mechanical, According to IEC/EN 60068-2-27
40 g, Mechanical, According to IEC/EN 60068-2-27, Sinusoidal shock 11 ms Climatic environmental conditions
Ambient operating temperature - min -25 °C Ambient operating temperature - max 60 °C Ambient operating temperature
(enclosed) - min 25 °C Am...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / Q25LTR-BL with the required quantity to info@electricaonline.com or use
electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd
Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification
requirements against the manufacturer documentation before purchase or installation.