

INDUSTRIAL COMPONENT DATA

M22-DL-A 167429 Y7-167429 EATON ELECTRIC Illuminated pushbutton actuator, flush, amber

Brand: EATON - MOELLER | Manufacturer Part Number: M22-DL-A



Manufacturer	EATON - MOELLER
MPN / Reference	M22-DL-A
Catalog number	Y7-167429
Category	Front element for push button
Minimum order	1 Pcs
Document ID	EO-7CEDA349DF
Generated	2026-08-01

Product Overview

Illuminated pushbutton actuator, flush, amber

M22-DL-A

Eaton Moeller® series M22 Illuminated pushbutton actuator, RMQ-Titan, Flush, momentary, orange, Blank, Bezel: titanium
Illuminated pushbutton actuator, Product range: RMQ-Titan, Single unit, Design: Flush, momentary, button plate: orange,
Button plate Blank, Degree of Protection: IP66, IP67, IP69K, Bezel: titanium, Connection to SmartWire-DT: yes, with
SWD-RMQ connections, Standards: IEC/EN 60947, VDE 0660

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Auxiliary Control and Signalling Elements
--------------	---

Additional Product Information

General specifications

Product Name Eaton Moeller® series M22 Illuminated pushbutton actuator Catalog Number 167429 Model Code M22-DL-A
EAN 4015081639298 Product Length/Depth 30 mm Product Height 30 mm Product Width 30 mm Product Weight 0.01 kg
Certifications VDE 0660

IEC/EN 60947

DNV

GL

LR Features & Functions

Bezel color Titanium Bezel material Plastic Design Flush

Classical Fitted with: Front ring Inscription Blank General

Degree of protection IP67

IP69K

IP66 Degree of protection (front side) IP67/IP69K

NEMA 4X Opening diameter 22.5 mm Product category RMQ-Titan Suitable for Illumination Type Illuminated pushbutton actuator Ambient conditions, mechanical

Mounting position As required Shock resistance Mechanical, According to IEC/EN 60068-2-27

30 g, Mechanical, According to IEC/EN 60068-2-27, Sinusoidal shock 11 ms Climatic environmental conditions

Ambient operating temperature - min -25 °C Ambient operating temperature - max 70 °C Climatic proofing Damp heat, cyclic, to IEC 60068-2-30

Damp heat, constant, to IEC 60068-2-78 Communication

Connection to SmartWire-DT With SWD-RMQ connections

Yes Actuator

Actuator color Orange Actuator function Spring-return

Momentary Contacts

Force for positive opening - min 0 N Design verification

Equipment heat dissipation, current-dependent P_{vid} 0 W Heat dissipation capacity P_{diss} 0 W Heat dissipation per pole, current-dependent P_{vid} 0 W Rated operational current for specified heat dissipation (I_n) 0 A Static heat dissipation, non-current-...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / M22-DL-A with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.