

INDUSTRIAL COMPONENT DATA

M22-DL-B 216931 Y7-216931 EATON ELECTRIC Illuminated pushbutton actuator, flush, blue, momentary

Brand: EATON - MOELLER | Manufacturer Part Number: M22-DL-B



Manufacturer	EATON - MOELLER
MPN / Reference	M22-DL-B
Catalog number	Y7-216931
Category	Front element for push button
Minimum order	1 Pcs
Document ID	EO-B612AF481A
Generated	2026-08-02

Product Overview

Illuminated pushbutton actuator, flush, blue, momentary

M22-DL-B

Eaton Moeller® series M22 Illuminated pushbutton actuator, RMQ-Titan, Flush, momentary, Blue, Blank, Bezel: titanium
Illuminated pushbutton actuator, Product range: RMQ-Titan, Single unit, Design: Flush, momentary, button plate: Blue,
Button plate Blank, Degree of Protection: IP66, IP67, IP69K, Bezel: titanium, Connection to SmartWire-DT: yes, with
SWD-RMQ connections, Front dimensions: 22 x 22, Standards: IEC/EN 60947, VDE 0660

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **EATON - MOELLER > Auxiliary Control and Signalling Elements**

Additional Product Information

General specifications

Product Name Eaton Moeller® series M22 Illuminated pushbutton actuator

Catalog Number 216931

Model Code M22-DL-B

EAN 4015082169312

Product Length/Depth 30 mm

Product Height 30 mm

Product Width 30 mm

Product Weight 0.01 kg

Compliances CE Marked

Certifications CSA Std. C22.2 No. 94-91

IEC 60947-5

CSA Std. C22.2 No. 14-05

UL 508

EN 60947-5

VDE

UL Category Control No.: NKCR

CSA Class No.: 3211-03

CSA-C22.2 No. 94-91

IEC/EN 60947

IEC/EN 60947-5

CSA-C22.2 No. 14-05

UL File No.: E29184

UL

CE

VDE 0660

CSA

CSA File No.: 012528

DNV

GL

LR

Features & Functions

Bezel color Titanium

Bezel material Plastic

Design Flush

Classical

Fitted with: Front ring

Inscription Blank

General information

Degree of protection IP66

NEMA 4X

NEMA 12

NEMA 13

IP67

NEMA 3R

IP69K

Degree of protection (front side) IP67/IP69K

NEMA 4X

Lifespan, mechanical 5,000,000 Operations

Opening diameter 22.5 mm

Operating frequency 3600 Operations/h

Product category RMQ-Titan

Product category RMQ-Titan

Size Front dimensions: 22 x 22 mm

Suitable for Illumination

Type Illuminated pushbutton actuator

Ambient conditions, mechanical

Mounting position As required

Shock resistance 30 g, Mechanical, According to IEC/EN 60068-2-27, Sinusoidal shock 11 ms

Mechanical, According to IEC/EN 60068-2-27

Climatic environmental conditions

Ambient operating temperature - min -25 °C

Ambient operating temperature - max 70 °C

Climatic proofing Damp heat, constant, to IEC 60068-2-78

Damp heat, cyclic, to IEC 60068-2-30

Communi...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / M22-DL-B with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.