

INDUSTRIAL COMPONENT DATA

M22S-DL-W-X1 216943 Y7-216943 EATON ELECTRIC

Illuminated pushbutton actuator, flush, white I, momentary

Brand: EATON - MOELLER | Manufacturer Part Number: M22S-DL-W-X1



Manufacturer	EATON - MOELLER
MPN / Reference	M22S-DL-W-X1
Catalog number	Y7-216943
Category	Front element for push button
Minimum order	10 Pcs
Document ID	EO-9F52D78823
Generated	2026-08-05

Product Overview

Illuminated pushbutton actuator, flush, white I, momentary

M22S-DL-W-X1

Eaton Moeller® series M22 Illuminated pushbutton actuator, RMQ-Titan, Flush, momentary, White, inscribed 1, Bezel: black
Illuminated pushbutton actuator, Product range: RMQ-Titan, Single unit, Design: Flush, momentary, button plate: White,
Button plate inscribed, Degree of Protection: IP66, IP67, IP69K, Bezel: black, Connection to SmartWire-DT: yes, with
SWD-RMQ connections, Front dimensions: 29,7, Standards: IEC/EN 60947, VDE 0660

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Auxiliary Control and Signalling Elements
--------------	---

Additional Product Information

General specifications

Product Name Eaton Moeller® series M22 Illuminated pushbutton actuator Catalog Number 216943 Model Code
M22S-DL-W-X1 EAN 4015082169435 Product Length/Depth 30 mm Product Height 30 mm Product Width 30 mm Product
Weight 0.01 kg Certifications CSA File No.: 012528

CSA Class No.: 3211-03

CSA

CSA-C22.2 No. 94-91

UL Category Control No.: NKCR

IEC/EN 60947

CE

UL File No.: E29184

CSA-C22.2 No. 14-05

UL 508

VDE 0660

IEC/EN 60947-5

UL

DNV

GL

LR Features & Functions

Bezel color Black Bezel material Plastic Design Flush

Classical Features Labelled Fitted with: Front ring Inscription Inscribed General

Degree of protection NEMA 13

IP67

NEMA 4X

NEMA 12

IP66

NEMA 3R

IP69K Degree of protection (front side) NEMA 4X

IP67/IP69K Lifespan, mechanical 5,000,000 Operations Opening diameter 22.5 mm Operating frequency 3600

Operations/h Product category RMQ-Titan Size Front diameter: 29.7 mm Suitable for Illumination Type Illuminated

pushbutton actuator Ambient conditions, mechanical

Mounting position As required Shock resistance 30 g, Mechanical, According to IEC/EN 60068-2-27, Sinusoidal shock 11 ms

Mechanical, According to IEC/EN 60068-2-27 Climatic environmental conditions

Ambient operating temperature - min -25 °C Ambient operating temperature - max 70 °C Climatic proofing Damp heat, cyclic, to IEC 60068-2-30

Damp heat, constant, to IEC 60068-2-78 Communication

Connection to SmartWire-DT Yes

With SWD-RMQ connections Actuator

Actuating force 5 N Actuator color White Actuator...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / M22S-DL-W-X1 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.