

INDUSTRIAL COMPONENT DATA

M22-DRL-W 216944 Y7-216944 EATON ELECTRIC Illuminated pushbutton actuator, flush, white, maintained

Brand: EATON - MOELLER | Manufacturer Part Number: M22-DRL-W



Manufacturer	EATON - MOELLER
MPN / Reference	M22-DRL-W
Catalog number	Y7-216944
Category	Front element for push button
Minimum order	5 Pcs
Document ID	EO-EB47312872
Generated	2026-08-04

Product Overview

Illuminated pushbutton actuator, flush, white, maintained

M22-DRL-W

Eaton Moeller® series M22 Illuminated pushbutton actuator, RMQ-Titan, Flush, maintained, White, Blank, Bezel: titanium Illuminated pushbutton actuator, Product range: RMQ-Titan, Single unit, Design: Flush, maintained, button plate: White, Button plate Blank, Degree of Protection: IP66, IP67, IP69K, Bezel: titanium, Connection to SmartWire-DT: yes, with SWD-RMQ connections, Front dimensions: 29,7, Instructions: Stay-put/spring-return function can be changed on device, Standards: IEC/EN 60947, VDE 0660

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Auxiliary Control and Signalling Elements
--------------	---

Additional Product Information

General specifications

Product Name Eaton Moeller® series M22 Illuminated pushbutton actuator Catalog Number 216944 Model Code M22-DRL-W EAN 4015082169442 Product Length/Depth 30 mm Product Height 30 mm Product Width 30 mm Product Weight 0.012 kg Compliances CE Marked Certifications CSA Std. C22.2 No. 14-05

EN 60947-5

IEC 60947-5

CSA Std. C22.2 No. 94-91

UL 508

VDE

CE

CSA-C22.2 No. 14-05

CSA-C22.2 No. 94-91

UL

UL Category Control No.: NKCR

IEC/EN 60947

CSA File No.: 012528

UL File No.: E29184

CSA Class No.: 3211-03

CSA

IEC/EN 60947-5

VDE 0660

DNV

GL

LR Features & Functions

Bezel color Titanium Bezel material Plastic Design Flush

Classical Fitted with: Front ring Functions Stay-put/spring-return function can be changed on device Inscription Blank

Material Titanium front ring General

Degree of protection IP69K

NEMA 12

NEMA 13

IP67

NEMA 3R

NEMA 4X

IP66 Degree of protection (front side) IP67/IP69K

NEMA 4X Lifespan, mechanical 1,000,000 Operations (AC operated) Opening diameter 22.5 mm Operating frequency 1800

Operations/h Product category RMQ-Titan Size Front diameter: 29.7 mm Suitable for Illumination Type Illuminated

pushbutton actuator Ambient conditions, mechanical

Mounting position As required Shock resistance 30 g, Mechanical, According to IEC/EN 60068-2-27, Sinusoidal shock 11 ms

Mechanical, According to IEC/EN 60068-2-27 Climatic environmental conditions

Ambient operating temperature - min -25 °C Ambient operating temperature - max 70 °C Climatic proofing Damp heat, cons...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / M22-DRL-W with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.