

INDUSTRIAL COMPONENT DATA

M22-DL-Y 216929 Y7-216929 EATON ELECTRIC Illuminated pushbutton actuator, flush, yellow, momentary

Brand: EATON - MOELLER | Manufacturer Part Number: M22-DL-Y



Manufacturer	EATON - MOELLER
MPN / Reference	M22-DL-Y
Catalog number	Y7-216929
Category	Front element for push button
Minimum order	1 Pcs
Document ID	EO-020BA09E77
Generated	2026-08-02

Product Overview

Illuminated pushbutton actuator, flush, yellow, momentary

M22-DL-Y

Illuminated pushbutton actuator, RMQ-Titan, Flush, momentary, yellow, Blank, Bezel: titanium

Illuminated pushbutton actuator, Product range: RMQ-Titan, Single unit, Design: Flush, momentary, button plate: yellow, Button plate Blank, Degree of Protection: IP66, IP67, IP69K, Bezel: titanium, Connection to SmartWire-DT: yes, with SWD-RMQ connections, Front dimensions: 22 x 22, Standards: IEC/EN 60947, VDE 0660

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Auxiliary Control and Signalling Elements
--------------	---

Additional Product Information

Illuminated pushbutton actuator, RMQ-Titan, Flush, momentary, yellow, Blank, Bezel: titanium
Illuminated pushbutton actuator, Product range: RMQ-Titan, Single unit, Design: Flush, momentary, button plate: yellow, Button plate Blank, Degree of Protection: IP66, IP67, IP69K, Bezel: titanium, Connection to SmartWire-DT: yes, with SWD-RMQ connections, Front dimensions: 22 x 22, Standards: IEC/EN 60947, VDE 0660

General specifications
Product nameEaton Moeller® series M22 Illuminated pushbutton actuator
Part no.M22-DL-YEAN4015082169299
Product Length/Depth30 millimetre
Product height30 millimetre
Product width30 millimetre
Product weight0.01 kilogram
CompliancesCE Marked
CertificationsIEC 60947-5
CSA Std. C22.2 No. 94-91
UL 508
EN 60947-5

CSA Std. C22.2 No. 14-05

VDE

CE

UL File No.: E29184

IEC/EN 60947

UL

CSA-C22.2 No. 14-05

CSA Class No.: 3211-03

IEC/EN 60947-5

VDE 0660

UL Category Control No.: NKCR

CSA File No.: 012528

CSA-C22.2 No. 94-91

CSA

DNV

GL

LRProduct TradenameM22Product TypeIlluminated pushbutton actuatorProduct Sub TypeNoneFeatures & FunctionsBezel colorTitaniumBezel materialPlasticDesignFlush

ClassicalFitted with:Front ringInscriptionBlankMaterialTitanium front ringGeneral informationDegree of protectionNEMA 12 IP69K

NEMA 4X

NEMA 13

IP67

IP66

NEMA 3RDegree of protection (front side)NEMA 4X

IP67/IP69KLifespan, mechanical5,000,000 OperationsOpening diameter22.5 mmOperating frequency3600

Operations/hProduct categoryRMQ-TitanSizeFront dimensions: 22 x 22 mmSuitable forIlluminatio...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / M22-DL-Y with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.