

INDUSTRIAL COMPONENT DATA

Q18LTR-GN 087831 Y7-87831 EATON ELECTRIC Illuminated pushbutton actuator, green, maintained

Brand: EATON - MOELLER | Manufacturer Part Number: Q18LTR-GN



Manufacturer	EATON - MOELLER
MPN / Reference	Q18LTR-GN
Catalog number	Y7-87831
Category	Front element for push button
Minimum order	10 Pcs
Document ID	EO-CF58698106
Generated	2026-08-04

Product Overview

Illuminated pushbutton actuator, green, maintained

Flush Illuminated Push Button 16 mm 18x18 mm Interlocking Green

Eaton Moeller® series RMQ16 Illuminated pushbutton actuator, green, maintained Q18LTR-GN

Illuminated pushbutton actuator, Product range: RMQ16, Single unit, Design: Flat, maintained, Description: without light elements, With base, W2x4,6d; max. 30 V, 1 W, button plate: green, Button plate Blank, Degree of Protection: IP65, Connection to SmartWire-DT: no, Front dimensions: 18 x 18

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Auxiliary Control and Signalling Elements
--------------	---

Additional Product Information

General specifications

Product Name Eaton Moeller® series RMQ16 Illuminated pushbutton actuator Catalog Number 087831 Model Code Q18LTR-GN EAN 4015080878315 Product Length/Depth 59 mm Product Height 18 mm Product Width 18 mm Product Weight 0.009 kg Certifications CSA Class No.: 3211-03
CSA-C22.2 No. 14-05
IEC/EN 60947-5
IEC/EN 60947
UL 508
UL Category Control No.: NKCR
CSA File No.: 46552

UL
UL File No.: E29184
CSA
CE Catalog Notes Filament bulb or LED needs to be ordered separately Features & Functions
Bezel color Black Bezel material Plastic Design Flat Inscription Blank General
Degree of protection IP65
NEMA 1 Degree of protection (front side) IP65
NEMA 1 Lifespan, mechanical 30,000,000 Operations Opening diameter 16 mm Operating frequency 1800 Operations/h
Overvoltage category III Pollution degree 3 Product category RMQ16 Rated impulse withstand voltage (Uimp) 800 V AC
Size Front dimensions: 18 x 18 mm Suitable for Illumination Terminal capacity 0.5 - 1.0 mm² Terminal size 2.8 x 0.8 mm to
DIN 46247 and IEC 60760, Fast-on connectors
2.8 x 0.8 mm to DIN 46244, Blade terminal Type Illuminated pushbutton actuator Ambient conditions, mechanical
Mounting position As required Shock resistance Mechanical, According to IEC/EN 60068-2-27
40 g, Mechanical, According to IEC/EN 60068-2-27, Sinusoidal shock 11 ms Climatic environmental conditions
Ambient operating temperature - min -25 °C Ambient operating temperature - max 60 °C Ambient operating temperature
(enclosed) - min 25 °C Am...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / Q18LTR-GN with the required quantity to info@electricaonline.com or use
electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd
Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification
requirements against the manufacturer documentation before purchase or installation.