

INDUSTRIAL COMPONENT DATA

M22-DRLH-R 216789 Y7-216789 EATON ELECTRIC Illuminated pushbutton actuator, raised, red, maintained

Brand: EATON - MOELLER | Manufacturer Part Number: M22-DRLH-R



Manufacturer	EATON - MOELLER
MPN / Reference	M22-DRLH-R
Catalog number	Y7-216789
Category	Front element for push button
Minimum order	5 Pcs
Document ID	EO-7C8E9B9CC0
Generated	2026-08-04

Product Overview

Illuminated pushbutton actuator, raised, red, maintained

M22-DRLH-R

Eaton Moeller® series M22 Illuminated pushbutton actuator, RMQ-Titan, Extended, maintained, red, Blank, Bezel: titanium
 Illuminated pushbutton actuator, Product range: RMQ-Titan, Single unit, Design: Extended, maintained, button plate: red,
 Button plate Blank, Degree of Protection: IP66, IP67, IP69K, Bezel: titanium, Connection to SmartWire-DT: yes, with
 SWD-RMQ connections, Front dimensions: 29,7, Instructions: Stay-put/spring-return function can be changed on device,
 Standards: IEC/EN 60947, VDE 0660

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Auxiliary Control and Signalling Elements
--------------	---

Additional Product Information

General specifications

Product Name Eaton Moeller® series M22 Illuminated pushbutton actuator Catalog Number 216789 Model Code
 M22-DRLH-R EAN 4015082167899 Product Length/Depth 30 mm Product Height 35 mm Product Width 30 mm Product
 Weight 0.013 kg Certifications CSA
 IEC/EN 60947-5
 UL File No.: E29184
 CE
 CSA-C22.2 No. 14-05
 UL 508

UL
VDE 0660
CSA Class No.: 3211-03
CSA File No.: 012528
CSA-C22.2 No. 94-91
IEC/EN 60947
UL Category Control No.: NKCR
DNV
GL
LR Features & Functions
Bezel color Titanium Bezel material Plastic Color Red Design Extended
Classical Fitted with: Front ring Functions Stay-put/spring-return function can be changed on device Inscription Blank
General
Degree of protection IP69K
IP67
NEMA 3R
NEMA 12
IP66
NEMA 13
NEMA 4X Degree of protection (front side) IP67/IP69K
NEMA 4X Lifespan, mechanical 1,000,000 Operations (AC operated) Opening diameter 22.5 mm Operating frequency 1800
Operations/h Product category RMQ-Titan Size Front diameter: 29.7 mm Suitable for Illumination Type Illuminated
pushbutton actuator Ambient conditions, mechanical
Mounting position As required Shock resistance 30 g, Mechanical, According to IEC/EN 60068-2-27, Sinusoidal shock 11
ms
Mechanical, According to IEC/EN 60068-2-27 Climatic environmental conditions
Ambient operating temperature - min -25 °C Ambient operating temperature - max 70 °C Climatic proofing Damp heat,
cyclic, to IEC 60068-2-30
Damp heat, constant, to IEC 60068-2-78 Communication
Connection to SmartWire-DT With SWD-RMQ...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / M22-DRLH-R with the required quantity to info@electricaonline.com or use
electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd
Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification
requirements against the manufacturer documentation before purchase or installation.