

## INDUSTRIAL COMPONENT DATA

# M22S-DLH-W-X1 216982 Y7-216982 EATON ELECTRIC

## Illuminated pushbutton actuator, raised, white I, momentary

Brand: EATON - MOELLER | Manufacturer Part Number: M22S-DLH-W-X1



|                 |                               |
|-----------------|-------------------------------|
| Manufacturer    | EATON - MOELLER               |
| MPN / Reference | M22S-DLH-W-X1                 |
| Catalog number  | Y7-216982                     |
| Category        | Front element for push button |
| Minimum order   | 1 Pcs                         |
| Document ID     | EO-6DB97A7539                 |
| Generated       | 2026-08-04                    |

### Product Overview

Illuminated pushbutton actuator, raised, white I, momentary

M22S-DLH-W-X1

Eaton Moeller® series M22 Illuminated pushbutton actuator, RMQ-Titan, Extended, momentary, White, inscribed 1, Bezel: black

Illuminated pushbutton actuator, Product range: RMQ-Titan, Single unit, Design: Extended, momentary, button plate: White, Button plate inscribed, Degree of Protection: IP66, IP67, IP69K, Bezel: black, Connection to SmartWire-DT: yes, with SWD-RMQ connections, Front dimensions: 29,7, Standards: IEC/EN 60947, VDE 0660

## STRUCTURED PRODUCT DATA

### Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

### Classification & Catalog Path

Catalog path

EATON - MOELLER &gt; Auxiliary Control and Signalling Elements

### Additional Product Information

General specifications

Product Name Eaton Moeller® series M22 Illuminated pushbutton actuator Catalog Number 216982 Model Code

M22S-DLH-W-X1 EAN 4015082169824 Product Length/Depth 30 mm Product Height 35 mm Product Width 30 mm Product

Weight 0.012 kg Certifications CSA-C22.2 No. 14-05

CSA

UL 508

IEC/EN 60947

CSA File No.: 012528

UL Category Control No.: NKCR

IEC/EN 60947-5

CE

VDE 0660

UL File No.: E29184

UL

CSA Class No.: 3211-03

CSA-C22.2 No. 94-91

DNV

GL

LR Features & Functions

Bezel color Black Bezel material Plastic Design Extended

Classical Features Labelled Fitted with: Front ring Inscription Inscribed General

Degree of protection IP69K

IP67

NEMA 3R

IP66

NEMA 4X

NEMA 13

NEMA 12 Degree of protection (front side) NEMA 4X

IP67/IP69K Lifespan, mechanical 5,000,000 Operations Opening diameter 22.5 mm Operating frequency 3600

Operations/h Product category RMQ-Titan Size Front diameter: 29.7 mm Suitable for Illumination Type Illuminated

pushbutton actuator Ambient conditions, mechanical

Mounting position As required Shock resistance 30 g, Mechanical, According to IEC/EN 60068-2-27, Sinusoidal shock 11 ms

Mechanical, According to IEC/EN 60068-2-27 Climatic environmental conditions

Ambient operating temperature - min -25 °C Ambient operating temperature - max 70 °C Climatic proofing Damp heat, cyclic, to IEC 60068-2-30

Damp heat, constant, to IEC 60068-2-78 Communication

Connection to SmartWire-DT Yes

With SWD-RMQ connections Actuator

Actuating force 5 N Actuator color White Ac...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / M22S-DLH-W-X1 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.