

INDUSTRIAL COMPONENT DATA

Q25LT-WS 086262 Y7-86262 EATON ELECTRIC Illuminated pushbutton actuator, white, momentary

Brand: EATON - MOELLER | Manufacturer Part Number: Q25LT-WS



Manufacturer	EATON - MOELLER
MPN / Reference	Q25LT-WS
Catalog number	Y7-86262
Category	Front element for push button
Minimum order	10 Pcs
Document ID	EO-A270068628
Generated	2026-08-02

Product Overview

Illuminated pushbutton actuator, white, momentary

Flush illuminated push-button 16 mm 25x25 mm White Return

Eaton Moeller® series RMQ16 Illuminated pushbutton actuator, white, momentary Q25LT-WS

Illuminated pushbutton actuator, Product range: RMQ16, Single unit, Design: Flat, momentary, Description: without light elements, With base, W2x4,6d; max. 30 V, 1 W, button plate: White, Button plate Blank, Degree of Protection: IP65, Connection to SmartWire-DT: no, Front dimensions: 25 x 25

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Auxiliary Control and Signalling Elements
--------------	---

Additional Product Information

General specifications

Product Name Eaton Moeller® series RMQ16 Illuminated pushbutton actuator Catalog Number 086262 Model Code Q25LT-WS EAN 4015080862628 Product Length/Depth 59 mm Product Height 25 mm Product Width 25 mm Product Weight 0.011 kg Certifications CE

IEC/EN 60947-5

UL

UL Category Control No.: NKCR

CSA File No.: 46552

CSA Class No.: 3211-03

CSA

CSA-C22.2 No. 14-05

UL 508

IEC/EN 60947

UL File No.: E29184 Catalog Notes Filament bulb or LED needs to be ordered separately Features & Functions

Bezel color Black Bezel material Plastic Design Flat Inscription Blank General

Degree of protection NEMA 1

IP65 Degree of protection (front side) NEMA 1

IP65 Lifespan, mechanical 3,000,000 Operations Opening diameter 16 mm Operating frequency 3600 Operations/h

Overvoltage category III Pollution degree 3 Product category RMQ16 Rated impulse withstand voltage (Uimp) 800 V AC

Size Front dimensions: 25 x 25 mm Suitable for Illumination Terminal size 2.8 x 0.8 mm to DIN 46247 and IEC 60760,

Fast-on connectors

2.8 x 0.8 mm to DIN 46244, Blade terminal Type Illuminated pushbutton actuator Ambient conditions, mechanical

Mounting position As required Shock resistance Mechanical, According to IEC/EN 60068-2-27

40 g, Mechanical, According to IEC/EN 60068-2-27, Sinusoidal shock 11 ms Climatic environmental conditions

Ambient operating temperature - min -25 °C Ambient operating temperature - max 60 °C Ambient operating temperature (enclosed) - min 25 °C Ambient operating temperature (enclo...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / Q25LT-WS with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.