

INDUSTRIAL COMPONENT DATA

Q25LT-WS/WB 090226 Y7-90226 EATON ELECTRIC

Illuminated pushbutton actuator, white, momentary, +filament lamp..

Brand: EATON - MOELLER | Manufacturer Part Number: Q25LT-WS/WB



Manufacturer	EATON - MOELLER
MPN / Reference	Q25LT-WS/WB
Catalog number	Y7-90226
Category	Front element for push button
Minimum order	10 Pcs
Document ID	EO-66ECDEAB08
Generated	2026-08-04

Product Overview

Illuminated pushbutton actuator, white, momentary, +filament lamp 24V

Flush Illuminated Push Button 16 mm 25x25 mm White Return With Lamp

Eaton Moeller® series RMQ16 Illuminated pushbutton actuator, white, momentary, +filament lamp 24V Q25LT-WS/WB

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Auxiliary Control and Signalling Elements
--------------	---

Additional Product Information

General specifications

Product Name Eaton Moeller® series RMQ16 Illuminated pushbutton actuator Catalog Number 090226 Model Code

Q25LT-WS/WB EAN 4015080902263 Product Length/Depth 59 mm Product Height 25 mm Product Width 25 mm Product Weight 0.011 kg Certifications CSA Class No.: 3211-03

IEC/EN 60947-5

CSA

IEC/EN 60947

CSA-C22.2 No. 14-05

CE

UL 508

UL Category Control No.: NKCR

CSA File No.: 46552

UL File No.: E29184

UL Features & Functions

Bezel color Black Bezel material Plastic Design Flat Fitted with: Filament bulb (24 V) Inscription Blank General

Degree of protection IP65

NEMA 1 Degree of protection (front side) IP65

NEMA 1 Lifespan, mechanical 3,000,000 Operations Opening diameter 16 mm Operating frequency 3600 Operations/h
Overvoltage category III Pollution degree 3 Product category RMQ16 Rated impulse withstand voltage (Uimp) 800 V AC
Size Front dimensions: 25 x 25 mm Suitable for Illumination Terminal size 2.8 x 0.8 mm to DIN 46244, Blade terminal
2.8 x 0.8 mm to DIN 46247 and IEC 60760, Fast-on connectors Type Illuminated pushbutton actuator Ambient conditions,
mechanical

Mounting position As required Shock resistance 40 g, Mechanical, According to IEC/EN 60068-2-27, Sinusoidal shock 11
ms

Mechanical, According to IEC/EN 60068-2-27 Climatic environmental conditions

Ambient operating temperature - min -25 °C Ambient operating temperature - max 60 °C Ambient operating temperature
(enclosed) - min 25 °C Ambient operating temperature (enclosed) - max 40 °C Climatic pro...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / Q25LT-WS/WB with the required quantity to info@electricaonline.com or use
electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd
Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification
requirements against the manufacturer documentation before purchase or installation.