

## INDUSTRIAL COMPONENT DATA

# Q25LT-X 051746 Y7-51746 EATON ELECTRIC Illuminated pushbutton actuator, without button plate, momentary

Brand: EATON - MOELLER | Manufacturer Part Number: Q25LT-X



|                 |                               |
|-----------------|-------------------------------|
| Manufacturer    | EATON - MOELLER               |
| MPN / Reference | Q25LT-X                       |
| Catalog number  | Y7-51746                      |
| Category        | Front element for push button |
| Minimum order   | 1 Pcs                         |
| Document ID     | EO-A9CEF5CB96                 |
| Generated       | 2026-08-01                    |

## Product Overview

Illuminated pushbutton actuator, without button plate, momentary

Flush light button. 16 mm. 25x25 mm. Return. No Indicator Plate

Illuminated pushbutton actuator, Product range: RMQ16, Single unit, Design: Flat, momentary, Description: without light elements, With base, W2x4,6d; max. 30 V, 1 W, Degree of Protection: IP65, Connection to SmartWire-DT: no, Front dimensions: 25 x 25

## STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

|              |                                                             |
|--------------|-------------------------------------------------------------|
| Catalog path | EATON - MOELLER > Auxiliary Control and Signalling Elements |
|--------------|-------------------------------------------------------------|

## Additional Product Information

Illuminated pushbutton actuator, without button plate, momentaryIlluminated pushbutton actuator, Product range: RMQ16, Single unit, Design: Flat, momentary, Description: without light elements, With base, W2x4,6d; max. 30 V, 1 W, Degree of Protection: IP65, Connection to SmartWire-DT: no, Front dimensions: 25 x 25

General specificationsProduct nameEaton Moeller® series RMQ16 Illuminated pushbutton actuatorPart no.Q25LT-XEAN4015080517467Product Length/Depth59 millimetreProduct height25 millimetreProduct width25 millimetreProduct weight0.011 kilogramCertificationsIEC/EN 60947-5

IEC/EN 60947

CSA Class No.: 3211-03

CE

CSA File No.: 46552

UL

CSA-C22.2 No. 14-05

UL 508

UL Category Control No.: NKCR

UL File No.: E29184

CSA Product Tradename RMQ16 Product Type Illuminated pushbutton actuator Product Sub Type None Catalog Notes Filament bulb or LED needs to be ordered separately Features & Functions Bezel color Black Bezel material Plastic Design Flat General information Degree of protection IP65

NEMA 1 Degree of protection (front side) NEMA 1

IP65 Lifespan, mechanical 3,000,000 Operations Opening diameter 16 mm Operating frequency 1800 Operations/h Overvoltage category III Pollution degree 3 Product category RMQ16 Size Front dimensions: 25 x 25 mm Rated impulse withstand voltage (Uimp) 800 V AC Suitable for Illumination Terminal size 2.8 x 0.8 mm to DIN 46244, Blade terminal

2.8 x 0.8 mm to DIN 46247 and IEC 60760, Fast-on connectors Type Illuminated pushbutton actuator Ambient conditions, mechanical Mounting position As requi...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / Q25LT-X with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.