

INDUSTRIAL COMPONENT DATA

M22-DGL-X 230961 Y7-230961 EATON ELECTRIC Illuminated pushbutton actuator, without button plate, protected

Brand: EATON - MOELLER | Manufacturer Part Number: M22-DGL-X



Manufacturer	EATON - MOELLER
MPN / Reference	M22-DGL-X
Catalog number	Y7-230961
Category	Front element for push button
Minimum order	5 Pcs
Document ID	EO-FB0A8023BC
Generated	2026-08-03

Product Overview

Illuminated pushbutton actuator, without button plate, protected

M22-DGL-X

Eaton Moeller® series M22 Illuminated pushbutton actuator, RMQ-Titan, Guard-ring, momentary, Without button plate, Bezel: titanium

Illuminated pushbutton actuator, Product range: RMQ-Titan, Single unit, Design: Guard-ring, momentary, button plate: Without button plate, Degree of Protection: IP66, IP67, IP69K, Bezel: titanium, Connection to SmartWire-DT: yes, with SWD-RMQ connections, Front dimensions: 29,7, Standards: IEC/EN 60947, VDE 0660

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Auxiliary Control and Signalling Elements
--------------	---

Additional Product Information

General specifications

Product Name Eaton Moeller® series M22 Illuminated pushbutton actuator Catalog Number 230961 Model Code M22-DGL-X EAN 4015082309619 Product Length/Depth 30 mm Product Height 30 mm Product Width 30 mm Product Weight 0.013 kg Compliances CE Marked Certifications IEC 60947-5

UL 508

CSA Std. C22.2 No. 14-05

EN 60947-5

CSA Std. C22.2 No. 94-91

VDE

UL
IEC/EN 60947-5
CSA-C22.2 No. 94-91
UL Category Control No.: NKCR
VDE 0660
CSA
CSA Class No.: 3211-03
CSA File No.: 012528
IEC/EN 60947
UL File No.: E29184
CE
CSA-C22.2 No. 14-05
DNV
GL
LR Features & Functions
Bezel color Titanium Bezel material Plastic Color None Design Guard-ring
Classical Fitted with: Front ring Material Titanium front ring General
Degree of protection IP69K
IP66
NEMA 3R
NEMA 4X
NEMA 13
IP67
NEMA 12 Degree of protection (front side) NEMA 4X
IP67/IP69K Lifespan, mechanical 5,000,000 Operations Opening diameter 22.5 mm Operating frequency 3600
Operations/h Product category RMQ-Titan Size Front diameter: 29.7 mm Suitable for Illumination Type Illuminated
pushbutton actuator Ambient conditions, mechanical
Mounting position As required Shock resistance 30 g, Mechanical, According to IEC/EN 60068-2-27, Sinusoidal shock 11
ms
Mechanical, According to IEC/EN 60068-2-27 Climatic environmental conditions
Ambient operating temperature - min -25 °C Ambient operating temperature - max 70 °C Climatic proofing Damp heat,
cyclic, to IEC 60068-2-30
Damp heat, constant, to IEC 60068-2-78 Communication
Connecti...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / M22-DGL-X with the required quantity to info@electricaonline.com or use
electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd
Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification
requirements against the manufacturer documentation before purchase or installation.