

INDUSTRIAL COMPONENT DATA

M22-WRLK3-G-2K10LED230-BVP 132598 Y7-132598 EATON ELECTRIC Selector switches 2 N/O with thumb grip, complete..

Brand: EATON - MOELLER | Manufacturer Part Number: M22-WRLK3-G-2K10LED230-BVP



Manufacturer	EATON - MOELLER
MPN / Reference	M22-WRLK3-G-2K10LED230-BVP
Catalog number	Y7-132598
Category	Front element for selector switch
Minimum order	1 Pcs
Document ID	EO-C9F7AC653D
Generated	2026-08-05

Product Overview

Selector switches 2 N/O with thumb grip, complete device

M22-WRLK3-G-2K10LED230-BVP

Eaton Moeller® series M22 Illuminated selector switch actuator, RMQ-Titan, maintained, 3 positions, green, Blister pack for hanging

Illuminated selector switch actuator, Product range: RMQ-Titan, Blister pack for hanging., Complete practical solution., Can be ordered using a single article no., Connection to SmartWire-DT: no

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path

EATON - MOELLER > Auxiliary Control and Signalling Elements

Additional Product Information

General specifications

Product Name Eaton Moeller® series M22 Illuminated selector switch actuator Catalog Number 132598 Model Code M22-WRLK3-G-2K10LED230-BVP EAN 4015081295333 Product Length/Depth 30 mm Product Height 210 mm Product Width 130 mm Product Weight 0.05 kg Compliances CE Features & Functions

Bezel color Titanium Bezel material Plastic Fitted with: Front ring General

Degree of protection NEMA 4X Degree of protection (front side) IP66 Lifespan, mechanical 100,000 Operations Opening diameter 22.5 mm Overvoltage category III Pollution degree 3 Size Front diameter: 29.7 mm Suitable for Illumination

Climatic environmental conditions

Ambient operating temperature - min -25 °C Ambient operating temperature - max 70 °C Actuator
Actuator color Black Actuator function Switching function latching Actuator type Toggle Number of switch positions 3
Contacts
Force for positive opening - min 0 N Design verification
Equipment heat dissipation, current-dependent P_{vid} 0 W Heat dissipation capacity P_{diss} 0 W Heat dissipation per pole,
current-dependent P_{vid} 0 W Rated operational current for specified heat dissipation (I_n) 0 A Static heat dissipation,
non-current-dependent P_{vs} 0 W 10.2.2 Corrosion resistance Meets the product standard's requirements. 10.2.3.1
Verification of thermal stability of enclosures Meets the product standard's requirements. 10.2.3.2 Verification of resistance
of insulating materials to normal heat Meets the product standard's requirements. 10.2.3.3 Resist. of...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / M22-WRLK3-G-2K10LED230-BVP with the required quantity to info@electricaonline.com or use
electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd
Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification
requirements against the manufacturer documentation before purchase or installation.