

INDUSTRIAL COMPONENT DATA

M22S-WLKV-W 284398 Y7-284398 EATON ELECTRIC

Illuminated selector switch actuator, 2 positions, white, moment..

Brand: EATON - MOELLER | Manufacturer Part Number: M22S-WLKV-W



Manufacturer	EATON - MOELLER
MPN / Reference	M22S-WLKV-W
Catalog number	Y7-284398
Category	Front element for selector switch
Minimum order	5 Pcs
Document ID	EO-CDC604FEC0
Generated	2026-08-05

Product Overview

Illuminated selector switch actuator, 2 positions, white, momentary

M22S-WLKV-W

Eaton Moeller® series M22 Illuminated selector switch actuator, RMQ-Titan, With thumb-grip, maintained, 2 positions (V position), White, Bezel: black

Illuminated selector switch actuator, Product range: RMQ-Titan, Single unit, Design: With thumb-grip, maintained, 2 positions (V position), Color Thumb-grip: White, Degree of Protection: IP66, Bezel: black, Connection to SmartWire-DT: yes, with SWD-RMQ connections, Front dimensions: 29,7, Instructions: Stay-put/spring-return function, can be changed with coding parts M22-XC-Y, Standards: IEC/EN 60947, VDE 0660, Degree of Protection: IP66

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Auxiliary Control and Signalling Elements

Additional Product Information

General specifications

Product Name Eaton Moeller® series M22 Illuminated selector switch actuator Catalog Number 284398 Model Code M22S-WLKV-W EAN 4015082843984 Product Length/Depth 46 mm Product Height 30 mm Product Width 30 mm Product Weight 0.014 kg Certifications CSA File No.: 012528

UL Category Control No.: NKCR

CSA-C22.2 No. 14-05

CSA-C22.2 No. 94-91

VDE 0660

IEC/EN 60947

UL File No.: E29184

CE

CSA Class No.: 3211-03

UL 508

CSA

IEC/EN 60947-5

UL Features & Functions

Bezel color Black Bezel material Plastic Design With thumb-grip Fitted with: Front ring Functions Stay-put/spring-return function, can be changed with coding parts M22-XC-Y General

Degree of protection NEMA 4X, 13 Degree of protection (front side) IP66 Lifespan, mechanical 100,000 Operations

Opening diameter 22.5 mm Operating frequency 2000 Operations/h Operating torque 0.3 Nm Overvoltage category III

Pollution degree 3 Product category RMQ-Titan Size Front diameter: 29.7 mm Suitable for Illumination Switching angle 60 °

Type Illuminated selector switch actuator Ambient conditions, mechanical

Mounting position As required Shock resistance 30 g, Mechanical, According to IEC/EN 60068-2-27, Sinusoidal shock 11 ms

Mechanical, According to IEC/EN 60068-2-27 Climatic environmental conditions

Ambient operating temperature - min -25 °C Ambient operating temperature - max 70 °C Climatic proofing Damp heat, cyclic, to IEC 60068-2-30

Damp heat, constant, to IEC 60068-2-78 Communication

Connection to SmartWire-DT With...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / M22S-WLKV-W with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.