

INDUSTRIAL COMPONENT DATA

M22S-WLK3-B 216842 Y7-216842 EATON ELECTRIC

Illuminated selector switch actuator, 3 positions, blue, momenta..

Brand: EATON - MOELLER | Manufacturer Part Number: M22S-WLK3-B



Manufacturer	EATON - MOELLER
MPN / Reference	M22S-WLK3-B
Catalog number	Y7-216842
Category	Front element for selector switch
Minimum order	1 Pcs
Document ID	EO-8B66C5AF59
Generated	2026-08-03

Product Overview

Illuminated selector switch actuator, 3 positions, blue, momentary

M22S-WLK3-B

Eaton Moeller® series M22 Illuminated selector switch actuator, RMQ-Titan, With thumb-grip, momentary, 3 positions, Blue, Bezel: black

Illuminated selector switch actuator, Product range: RMQ-Titan, Single unit, Design: With thumb-grip, momentary, 3 positions, Color Thumb-grip: Blue, Degree of Protection: IP66, Bezel: black, Connection to SmartWire-DT: yes, with SWD-RMQ connections, Front dimensions: 29,7, Instructions: Stay-put/spring-return function, can be changed with coding parts M22-XC-Y, Standards: IEC/EN 60947, VDE 0660, Degree of Protection: IP66

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Auxiliary Control and Signalling Elements
--------------	---

Additional Product Information

General specifications

Product Name Eaton Moeller® series M22 Illuminated selector switch actuator Catalog Number 216842 Model Code M22S-WLK3-B EAN 4015082168421 Product Length/Depth 46 mm Product Height 30 mm Product Width 30 mm Product Weight 0.013 kg Certifications IEC/EN 60947-5

CSA

CSA-C22.2 No. 94-91

UL
UL 508
UL Category Control No.: NKCR
IEC/EN 60947
UL File No.: E29184
VDE 0660
CE
CSA Class No.: 3211-03
CSA-C22.2 No. 14-05
CSA File No.: 012528
DNV
GL
LR Catalog Notes M22S-WLK3-B Features & Functions
Bezel color Black Bezel material Plastic Design With thumb-grip
Classical Fitted with: Front ring Functions Stay-put/spring-return function, can be changed with coding parts M22-XC-Y
General
Degree of protection NEMA 4X, 13 Degree of protection (front side) IP66 Lifespan, mechanical 100,000 Operations
Opening diameter 22.5 mm Operating frequency 2000 Operations/h Operating torque 0.3 Nm Overvoltage category III
Pollution degree 3 Product category RMQ-Titan Size Front diameter: 29.7 mm Suitable for Illumination Switching angle 40 °
Ambient conditions, mechanical
Mounting position As required Shock resistance 30 g, Mechanical, According to IEC/EN 60068-2-27, Sinusoidal shock 11 ms
Mechanical, According to IEC/EN 60068-2-27 Climatic environmental conditions
Ambient operating temperature - min -25 °C Ambient operating temperature - max 70 °C Climatic proofing Damp heat, cyclic, to IEC 60068-2-30
Damp heat, constant, to IEC 60068-2-78 Communication
Connection to SmartWire-DT....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / M22S-WLK3-B with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.