

**INDUSTRIAL COMPONENT DATA**

# Q25LWK3R1-GN 072366 Y7-72366 EATON ELECTRIC

## Illuminated selector switch actuator, 3 positions, green, mainta..

Brand: EATON - MOELLER | Manufacturer Part Number: Q25LWK3R1-GN



|                 |                                   |
|-----------------|-----------------------------------|
| Manufacturer    | EATON - MOELLER                   |
| MPN / Reference | Q25LWK3R1-GN                      |
| Catalog number  | Y7-72366                          |
| Category        | Front element for selector switch |
| Minimum order   | 1 Pcs                             |
| Document ID     | EO-3F2C200E35                     |
| Generated       | 2026-08-05                        |

### Product Overview

Illuminated selector switch actuator, 3 positions, green, maintained

Dimmer 16 mm 25x25 mm 3 positions Interlock Green

Eaton Moeller® series RMQ16 Illuminated selector switch actuator, maintained/momentary, 45°, 25 x 25 mm, 3 positions, With thumb-grip, green, with VS anti-rotation tab, without light elements, With base, W2x4,6d; max. 30 V Q25LWK3R1-GN Illuminated selector switch actuator, Product range: RMQ16, Single unit, Design: With thumb-grip, maintained/momentary, with VS anti-rotation tab, without light elements, With base, W2x4,6d; max. 30 V, 1 W, 3 positions, Color Thumb-grip: green, Degree of Protection: IP65, Connection to SmartWire-DT: no, Front dimensions: 25 × 25 mm, Degree of Protection: IP65

**STRUCTURED PRODUCT DATA**

### Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

### Classification & Catalog Path

|              |                                                             |
|--------------|-------------------------------------------------------------|
| Catalog path | EATON - MOELLER > Auxiliary Control and Signalling Elements |
|--------------|-------------------------------------------------------------|

### Additional Product Information

General specifications

Product Name Eaton Moeller® series RMQ16 Illuminated selector switch actuator Catalog Number 072366 Model Code Q25LWK3R1-GN EAN 4015080723660 Product Length/Depth 75 mm Product Height 25 mm Product Width 25 mm Product Weight 0.017 kg Certifications CSA-C22.2 No. 14-05

UL 508

CE

IEC/EN 60947-5

CSA File No.: 46552

IEC/EN 60947

CSA Class No.: 3211-03

CSA

UL Category Control No.: NKCR

UL File No.: E29184

UL Catalog Notes Filament bulb or LED needs to be ordered separately Features & Functions

Bezel color Black Bezel material Plastic Design With thumb-grip Fitted with: VS anti-rotation tab General

Degree of protection NEMA 1 Degree of protection (front side) IP65 Lifespan, mechanical 3,000,000 Operations Opening diameter 16 mm Operating frequency 1800 Operations/h Operating torque 0.2 Nm Overvoltage category III Pollution degree 3 Product category RMQ16 Rated impulse withstand voltage (Uimp) 800 V AC Size Front dimensions: 25 × 25 mm Suitable for Illumination Switching angle 45 ° Terminal capacity 0.5 - 1.0 mm<sup>2</sup> Terminal size 2.8 x 0.8 mm to DIN 46247 and IEC 60760, Fast-on connectors

2.8 x 0.8 mm to DIN 46244, Blade terminal Type Illuminated selector switch actuator Ambient conditions, mechanical

Mounting position As required Shock resistance Mechanical, According to IEC/EN 60068-2-27

40 g, Mechanical, According to IEC/EN 60068-2-27, Sinusoidal shock 11 ms Climatic environmental conditions

Ambient operating temperature - min -25 °C Ambient operating tempera...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / Q25LWK3R1-GN with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.