

INDUSTRIAL COMPONENT DATA

M22-WRLK3-G 216847 Y7-216847 EATON ELECTRIC

Illuminated selector switch actuator, 3 positions, green, mainta..

Brand: EATON - MOELLER | Manufacturer Part Number: M22-WRLK3-G



Manufacturer	EATON - MOELLER
MPN / Reference	M22-WRLK3-G
Catalog number	Y7-216847
Category	Front element for selector switch
Minimum order	1 Pcs
Document ID	EO-F43AE560B2
Generated	2026-08-05

Product Overview

Illuminated selector switch actuator, 3 positions, green, maintained

M22-WRLK3-G

Eaton Moeller® series M22 Illuminated selector switch actuator, RMQ-Titan, With thumb-grip, maintained, 3 positions, green, Bezel: titanium

Illuminated selector switch actuator, Product range: RMQ-Titan, Single unit, Design: With thumb-grip, maintained, 3 positions, Color Thumb-grip: green, Degree of Protection: IP66, Bezel: titanium, Connection to SmartWire-DT: yes, with SWD-RMQ connections, Front dimensions: 29,7, Instructions: Stay-put/spring-return function, can be changed with coding parts M22-XC-Y, Standards: IEC/EN 60947, VDE 0660, Degree of Protection: IP66

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Auxiliary Control and Signalling Elements

Additional Product Information

General specifications

Product Name Eaton Moeller® series M22 Illuminated selector switch actuator

Catalog Number 216847

Model Code M22-WRLK3-G

EAN 4015082168476

Product Length/Depth 46 mm

Product Height 30 mm
Product Width 30 mm
Product Weight 0.013 kg
Compliances CE Marked
Certifications CSA Std. C22.2 No. 94-91
IEC 60947-5
UL 508
CSA Std. C22.2 No. 14-05
EN 60947-5
VDE
CSA
UL
UL Category Control No.: NKCR
CSA File No.: 012528
VDE 0660
CE
UL File No.: E29184
CSA-C22.2 No. 14-05
IEC/EN 60947
CSA Class No.: 3211-03
CSA-C22.2 No. 94-91
IEC/EN 60947-5
Features & Functions
Bezel color Titanium
Bezel material Plastic
Color Black
Green
Design With thumb-grip
Fitted with: Front ring
Functions Stay-put/spring-return function, can be changed with coding parts M22-XC-Y
General information
Accessories Thumb grip
Degree of protection NEMA 4X, 13
Degree of protection (front side) IP66
Lifespan, mechanical 100,000 Operations
Opening diameter 22.5 mm
Operating frequency 2000 Operations/h
Operating torque 0.3 Nm
Overvoltage category III
Pollution degree 3
Product category RMQ-Titan
Product category RMQ-Titan
Size Front diameter: 29.7 mm
Suitable for Illumination
Switching angle 60 °
Type Illuminated selector switch actuator
Ambient conditions, mechanical

Mounting position As required

Shock resistance Mechanical, According to IEC/EN 60068-2-27

30 g, Mechanical, According to IEC/EN 60068-2-27, Sinusoidal shock 11 ms

Climatic environmental conditions

Ambient operating temperature - min -25 °C...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / M22-WRLK3-G with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.