

## INDUSTRIAL COMPONENT DATA

# M22-WLK3-G 216837 Y7-216837 EATON ELECTRIC Illuminated selector switch actuator, 3 positions, green, momenta..

Brand: EATON - MOELLER | Manufacturer Part Number: M22-WLK3-G



|                 |                                   |
|-----------------|-----------------------------------|
| Manufacturer    | EATON - MOELLER                   |
| MPN / Reference | M22-WLK3-G                        |
| Catalog number  | Y7-216837                         |
| Category        | Front element for selector switch |
| Minimum order   | 5 Pcs                             |
| Document ID     | EO-32036D2652                     |
| Generated       | 2026-08-03                        |

## Product Overview

Illuminated selector switch actuator, 3 positions, green, momentary

M22-WLK3-G

Eaton Moeller® series M22 Illuminated selector switch actuator, RMQ-Titan, With thumb-grip, momentary, 3 positions, green, Bezel: titanium

Illuminated selector switch actuator, Product range: RMQ-Titan, Single unit, Design: With thumb-grip, momentary, 3 positions, Color Thumb-grip: green, Degree of Protection: IP66, Bezel: titanium, Connection to SmartWire-DT: yes, with SWD-RMQ connections, Front dimensions: 29,7, Instructions: Stay-put/spring-return function, can be changed with coding parts M22-XC-Y, Standards: IEC/EN 60947, VDE 0660, Degree of Protection: IP66

## STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

Catalog path

EATON - MOELLER &gt; Auxiliary Control and Signalling Elements

## Additional Product Information

General specifications

Product Name Eaton Moeller® series M22 Illuminated selector switch actuator Catalog Number 216837 Model Code M22-WLK3-G EAN 4015082168377 Product Length/Depth 46 mm Product Height 30 mm Product Width 30 mm Product Weight 0.013 kg Compliances CE Marked Certifications UL 508

CSA Std. C22.2 No. 94-91

CSA Std. C22.2 No. 14-05

IEC 60947-5

EN 60947-5

CSA File No.: 012528

UL Category Control No.: NKCR

CSA

IEC/EN 60947

CSA Class No.: 3211-03

UL File No.: E29184

VDE 0660

CSA-C22.2 No. 14-05

IEC/EN 60947-5

CE

CSA-C22.2 No. 94-91

UL

DNV

GL

LR Features & Functions

Bezel color Titanium Bezel material Plastic Color Green Design With thumb-grip

Classical Fitted with: Front ring Functions Stay-put/spring-return function, can be changed with coding parts M22-XC-Y  
General

Accessories Thumb grip Degree of protection NEMA 4X, 13 Degree of protection (front side) IP66 Lifespan, mechanical  
100,000 Operations Opening diameter 22.5 mm Operating frequency 2000 Operations/h Operating torque 0.3 Nm  
Overvoltage category III Pollution degree 3 Product category RMQ-Titan Size Front diameter: 29.7 mm Suitable for  
Illumination Switching angle 40 ° Type Illuminated selector switch actuator Ambient conditions, mechanical  
Mounting position As required Shock resistance 30 g, Mechanical, According to IEC/EN 60068-2-27, Sinusoidal shock 11  
ms

Mechanical, According to IEC/EN 60068-2-27 Climatic environmental conditions

Ambient operating temperature - min -25 °C Ambient operating temperature...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / M22-WLK3-G with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use  
[electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd  
Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification  
requirements against the manufacturer documentation before purchase or installation.