

INDUSTRIAL COMPONENT DATA

M22-WLK3-Y 216839 Y7-216839 EATON ELECTRIC Illuminated selector switch actuator, 3 positions, yellow, moment..

Brand: EATON - MOELLER | Manufacturer Part Number: M22-WLK3-Y



Manufacturer	EATON - MOELLER
MPN / Reference	M22-WLK3-Y
Catalog number	Y7-216839
Category	Front element for selector switch
Minimum order	5 Pcs
Document ID	EO-193C9E55EA
Generated	2026-08-03

Product Overview

Illuminated selector switch actuator, 3 positions, yellow, momentary

M22-WLK3-Y

Eaton Moeller® series M22 Illuminated selector switch actuator, RMQ-Titan, With thumb-grip, momentary, 3 positions, yellow, Bezel: titanium

Illuminated selector switch actuator, Product range: RMQ-Titan, Single unit, Design: With thumb-grip, momentary, 3 positions, Color Thumb-grip: yellow, Degree of Protection: IP66, Bezel: titanium, Connection to SmartWire-DT: yes, with SWD-RMQ connections, Front dimensions: 29,7, Instructions: Stay-put/spring-return function, can be changed with coding parts M22-XC-Y, Standards: IEC/EN 60947, VDE 0660, Degree of Protection: IP66

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Auxiliary Control and Signalling Elements
--------------	---

Additional Product Information

General specifications

Product Name Eaton Moeller® series M22 Illuminated selector switch actuator Catalog Number 216839 Model Code M22-WLK3-Y EAN 4015082168391 Product Length/Depth 46 mm Product Height 30 mm Product Width 30 mm Product Weight 0.013 kg Compliances CE Marked Certifications EN 60947-5

CSA Std. C22.2 No. 94-91

UL 508

CSA Std. C22.2 No. 14-05

IEC 60947-5

VDE

IEC/EN 60947

CSA Class No.: 3211-03

UL Category Control No.: NKCR

CE

CSA File No.: 012528

CSA-C22.2 No. 14-05

UL File No.: E29184

CSA

VDE 0660

IEC/EN 60947-5

UL

CSA-C22.2 No. 94-91 Features & Functions

Bezel color Titanium Bezel material Plastic Color Yellow Design With thumb-grip Fitted with: Front ring Functions

Stay-put/spring-return function, can be changed with coding parts M22-XC-Y General

Accessories Thumb grip Degree of protection NEMA 4X, 13 Degree of protection (front side) IP66 Lifespan, mechanical

100,000 Operations Opening diameter 22.5 mm Operating frequency 2000 Operations/h Operating torque 0.3 Nm

Overvoltage category III Pollution degree 3 Product category RMQ-Titan Size Front diameter: 29.7 mm Suitable for

Illumination Switching angle 40 ° Type Illuminated selector switch actuator Ambient conditions, mechanical

Mounting position As required Shock resistance 30 g, Mechanical, According to IEC/EN 60068-2-27, Sinusoidal shock 11 ms

Mechanical, According to IEC/EN 60068-2-27 Climatic environmental conditions

Ambient operating temperature - min -25 °C Ambient operating temperature - max 70 °C Cl...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / M22-WLK3-Y with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.