

INDUSTRIAL COMPONENT DATA

M22S-WRK3-* 217437 Y7-217437 EATON ELECTRIC Selector switch, toggle, 3 positions, black, maintained, non-sta..

Brand: EATON - MOELLER | Manufacturer Part Number: M22S-WRK3-*



Manufacturer	EATON - MOELLER
MPN / Reference	M22S-WRK3-*
Catalog number	Y7-217437
Category	Front element for selector switch
Minimum order	1 Pcs
Document ID	EO-D9A9009702
Generated	2026-08-01

Product Overview

Selector switch, toggle, 3 positions, black, maintained, non-standard inscription

M22S-WRK3-*

Eaton Moeller® series M22 Changeover switch, RMQ-Titan, With thumb-grip, maintained, 3 positions, selectable, Bezel: black

Changeover switch, Product range: RMQ-Titan, Single unit, Design: With thumb-grip, maintained, 3 positions, Degree of Protection: IP66, Bezel: black, Connection to SmartWire-DT: yes, with SWD-RMQ connections, Front dimensions: 29,7, Instructions: Stay-put/spring-return function, can be changed with coding parts M22-XC-Y, with plunger bridge for the middle contact, Standards: IEC/EN 60947, VDE 0660, Degree of Protection: IP66

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path

EATON - MOELLER > Auxiliary Control and Signalling Elements

Additional Product Information

General specifications

Product Name Eaton Moeller® series M22 Selector switch Catalog Number 217437 Model Code M22S-WRK3-* Product Length/Depth 46 mm Product Height 30 mm Product Width 30 mm Product Weight 0.013 kg Certifications CSA File No.: 012528

CSA

CSA-C22.2 No. 94-91

UL 508

IEC/EN 60947

IEC/EN 60947-5

VDE 0660

CE

CSA-C22.2 No. 14-05

UL File No.: E29184

CSA Class No.: 3211-03

UL Category Control No.: NKCR

UL

DNV

GL

LR Features & Functions

Bezel color Black Bezel material Plastic Design With thumb-grip

Classical Fitted with: Front ring

Plunger bridge for the middle contact Functions Stay-put/spring-return function, can be changed with coding parts

M22-XC-Y General

Degree of protection NEMA 4X, 13 Degree of protection (front side) IP66 Lifespan, mechanical 100,000 Operations

Opening diameter 22.5 mm Operating frequency 2000 Operations/h Operating torque 0.3 Nm Overvoltage category III

Pollution degree 3 Product category RMQ-Titan Size Front diameter: 29.7 mm Type Selector switch actuator Ambient conditions, mechanical

Mounting position As required Shock resistance 30 g, Mechanical, According to IEC/EN 60068-2-27, Sinusoidal shock 11 ms

Mechanical, According to IEC/EN 60068-2-27 Climatic environmental conditions

Ambient operating temperature - min -25 °C Ambient operating temperature - max 70 °C Ambient storage temperature - min 40 °C Ambient storage temperature - max 80 °C Climatic proofing Damp heat, constant, to IEC 60068-2-78

Damp heat, cyclic, to IEC 60068-2-30 Commu...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / M22S-WRK3-* with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.