

INDUSTRIAL COMPONENT DATA

Z-S230/S 265262 Y7-265262 EATON ELECTRIC Impulse relay, 230AC, 1 N/O, 16A, 50Hz, 1HP

Brand: EATON - MOELLER | Manufacturer Part Number: Z-S230/S



Manufacturer	EATON - MOELLER
MPN / Reference	Z-S230/S
Catalog number	Y7-265262
Category	Latching relay
Minimum order	1 Pcs
Document ID	EO-B73554AE8A
Generated	2026-08-05

Product Overview

Impulse relay, 230AC, 1 N/O, 16A, 50Hz, 1HP

Z-S230/S

Eaton Z-S Impulse relay, 230AC, 1 N/O, 16A, 50Hz, 1HP

Impulse relay, control voltage 230V 50Hz, function: 1 N/O, rated operational current at 250V AC according to IEC/EN 60669-2-2: 16A, standard front dimension 45 mm, mounting width 1 SU (17.5mm), top-hat rail mounting, terminal cross-section 0.5-10 mm² solid and flexible / 0.5-6 mm² flexible with ferrule

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Modular Switchgear - Others and Accessories

Additional Product Information

General specifications

Product Name Eaton Z-S impulse relay

Catalog Number 265262

Model Code Z-S230/S

EAN 4015082652623

Product Length/Depth 80 mm

Product Height 70 mm

Product Width 17.5 mm

Product Weight 0.131 kg

Compliances RoHS conform

Certifications CE

Product specifications

Number of poles Single-pole

Mounting method DIN rail

Control voltage 1 type AC

Ambient operating temperature - max 45 °C

Ambient operating temperature - min -20 °C

Control voltage 1 - max 230 V

Control voltage 1 - min 230 V

Control voltage 2 - max 0 V

Control voltage 2 - min 0 V

Frequency control voltage 1 - max 50 Hz

Frequency control voltage 1 - min 50 Hz

Frequency control voltage 2 - max 0 Hz

Frequency control voltage 2 - min 0 Hz

Heat dissipation per pole, current-dependent 1.5 W

Incandescent lamp load - max 1980 W

Load fluorescent lamp - max 1020 VA

Load fluorescent lamp (duo circuit) - max 1820 VA

Load fluorescent lamp (parallel compensated) - max 1105 VA

Number of contacts (change-over contacts) 0

Number of contacts (normally closed contacts) 0

Number of contacts (normally open contacts) 1

Rated operational current for specified heat dissipation (In) 16 A

Rated switch current 16 A

Equipment heat dissipation, current-dependent 1.5 W

Supply voltage - max 250 V

Supply voltage - min 24 V

Switching current (cos phi = 0.6) - max 24 A

Width in number of modular spacings 1

Built-in depth 60 mm

Operating mode Manual operation possible

Control voltage 2 type AC

Voltage type AC

Functions Mechanical switc...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / Z-S230/S with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.