

**INDUSTRIAL COMPONENT DATA**

# IN32B3-20F-1 EP-500103 Y7-500103 EATON ELECTRIC IN32B, 3 poles, 2000 A, fixed mounting

Brand: EATON - MOELLER | Manufacturer Part Number: IN32B3-20F-1



|                 |                     |
|-----------------|---------------------|
| Manufacturer    | EATON - MOELLER     |
| MPN / Reference | IN32B3-20F-1        |
| Catalog number  | Y7-500103           |
| Category        | Switch disconnecter |
| Minimum order   | 1 Pcs               |
| Document ID     | EO-968D242FDE       |
| Generated       | 2026-08-01          |

## Product Overview

IN32B, 3 poles, 2000 A, fixed mounting

IN32B3-20F-1 . Switch-disconnector, 3p, 2000A, fixed

Switch-disconnector, 3p, 2000A, fixed

**STRUCTURED PRODUCT DATA**

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

Catalog path **EATON - MOELLER > Circuit Breakers IZM**

## Additional Product Information

**General specifications**

Product Name Eaton IZM32/IN32 switch-disconnector Catalog Number EP-500103 Model Code IN32B3-20F-1 EAN 9010653017288 Product Length/Depth 511 mm Product Height 514 mm Product Width 492 mm Product Weight 60.325 kg  
Compliances RoHS conform Certifications CE Product specifications

Features Motor drive optional

Version as main switch Actuator color Green Rated uninterrupted current (Iu) 2000 A Device construction Built-in device  
fixed built-in technique Rated short-time withstand current (Icw) 65 kA Electrical connection type of main circuit Rail  
connection Actuator type Push button Number of auxiliary contacts (change-over contacts) 4 Number of auxiliary contacts  
(normally closed contacts) 0 Number of auxiliary contacts (normally open contacts) 0 Switching power at 400 V 0 kW  
Number of poles Three-pole Degree of protection (front side) IP20 Functions Interlockable

Voltage release optional Suitable for Distribution board installation

Floor mounting Rated operating power at AC-23, 400 V 0 kW Rated operating power at AC-3, 400 V 0 kW Rated operating  
voltage (Ue) - min 440 V Rated operating voltage (Ue) at AC - max 690 V Rated permanent current at AC-21, 400 V 2000 A

Rated permanent current at AC-23, 400 V 2000 A

ETIM for EP-500103 Low-voltage industrial controls and switchgear (EC000216)

Feature Name

Feature Value

Version as main switch (EF006981)

Yes

Version as maintenance-/service switch (EF006986)

No

Version as safety switch (EF006985)

No

Version as emerg...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / IN32B3-20F-1 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.