

**INDUSTRIAL COMPONENT DATA**

# IN32B3-25W-1 EP-500106 Y7-500106 EATON ELECTRIC IN32B, 3-pole, 2500 A, removable

Brand: EATON - MOELLER | Manufacturer Part Number: IN32B3-25W-1



|                 |                     |
|-----------------|---------------------|
| Manufacturer    | EATON - MOELLER     |
| MPN / Reference | IN32B3-25W-1        |
| Catalog number  | Y7-500106           |
| Category        | Switch disconnecter |
| Minimum order   | 1 Pcs               |
| Document ID     | EO-0FDA444DF1       |
| Generated       | 2026-08-05          |

## Product Overview

IN32B, 3-pole, 2500 A, removable  
IN32B3-25W-1 . Switch-disconnector, 3p, 2500A, withdrawable part  
Switch-disconnector, 3p, 2500A, withdrawable part

**STRUCTURED PRODUCT DATA**

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

|              |                                        |
|--------------|----------------------------------------|
| Catalog path | EATON - MOELLER > Circuit Breakers IZM |
|--------------|----------------------------------------|

## Additional Product Information

**General specifications**

Product Name Eaton IZM32/IN32 switch-disconnector Catalog Number EP-500106 Model Code IN32B3-25W-1 EAN 9010653017301 Product Length/Depth 511 mm Product Height 514 mm Product Width 492 mm Product Weight 86.925 kg  
Compliances RoHS conform Certifications CE Product specifications  
Features Motor drive optional  
Version as main switch Actuator color Green Rated uninterrupted current (Iu) 2500 A Device construction Built-in device slide-in technique (withdrawable) Rated short-time withstand current (Icw) 65 kA Electrical connection type of main circuit Rail connection Actuator type Push button Number of auxiliary contacts (change-over contacts) 4 Number of auxiliary contacts (normally closed contacts) 0 Number of auxiliary contacts (normally open contacts) 0 Switching power at 400 V 0 kW Number of poles Three-pole Degree of protection (front side) IP20 Functions Interlockable  
Voltage release optional Position of connection for main current circuit Back side Suitable for Distribution board installation Floor mounting Rated operating power at AC-23, 400 V 0 kW Rated operating power at AC-3, 400 V 0 kW Rated operating voltage (Ue) - min 440 V Rated operating voltage (Ue) at AC - max 690 V Rated permanent current at AC-21, 400 V 2500 A

Rated permanent current at AC-23, 400 V 2500 A

ETIM for EP-500106 Low-voltage industrial controls and switchgear (EC000216)

Feature Name

Feature Value

Version as main switch (EF006981)

Yes

Version as maintenance-/service switch (E...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / IN32B3-25W-1 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.