

INDUSTRIAL COMPONENT DATA

IN32N3-12W-1 EP-500130 Y7-500130 EATON ELECTRIC IN32N, 3-pole, 1250 A, removable

Brand: EATON - MOELLER | Manufacturer Part Number: IN32N3-12W-1



Manufacturer	EATON - MOELLER
MPN / Reference	IN32N3-12W-1
Catalog number	Y7-500130
Category	Switch disconnecter
Minimum order	1 Pcs
Document ID	EO-9B72D701BE
Generated	2026-08-04

Product Overview

IN32N, 3-pole, 1250 A, removable

IN32N3-12W-1 . Switch-disconnector, 3p, 1250A, withdrawable part

Switch-disconnector, 3p, 1250A, withdrawable part

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **EATON - MOELLER > Circuit Breakers IZM**

Additional Product Information

General specifications

Product Name Eaton IZM32/IN32 switch-disconnector Catalog Number EP-500130 Model Code IN32N3-12W-1 EAN 9010653017547 Product Length/Depth 511 mm Product Height 514 mm Product Width 492 mm Product Weight 71.725 kg
Compliances RoHS conform Certifications CE Product specifications

Features Motor drive optional

Version as main switch Actuator color Green Rated uninterrupted current (Iu) 1250 A Device construction Built-in device
slide-in technique (withdrawable) Rated short-time withstand current (Icw) 85 kA Electrical connection type of main circuit
Rail connection Actuator type Push button Number of auxiliary contacts (change-over contacts) 4 Number of auxiliary
contacts (normally closed contacts) 0 Number of auxiliary contacts (normally open contacts) 0 Switching power at 400 V 0
kW Number of poles Three-pole Degree of protection (front side) IP20 Functions Interlockable

Voltage release optional Position of connection for main current circuit Back side Suitable for Distribution board installation
Floor mounting Rated operating power at AC-23, 400 V 0 kW Rated operating power at AC-3, 400 V 0 kW Rated operating
voltage (Ue) - min 440 V Rated operating voltage (Ue) at AC - max 690 V Rated permanent current at AC-21, 400 V 1250 A

Rated permanent current at AC-23, 400 V 1250 A

ETIM for EP-500130 Low-voltage industrial controls and switchgear (EC000216)

Feature Name

Feature Value

Version as main switch (EF006981)

Yes

Version as maintenance-/service switch (E...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / IN32N3-12W-1 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.