

CSA-C22.2 No. 14-05

UL 508 General

Product category Accessories Suitable for Round conductor connection

Other Climatic environmental conditions

Ambient operating temperature - min -25 °C Ambient operating temperature - max 60 °C Terminal capacities

Terminal capacity (flexible with ferrule AWG) 14 - 8 Terminal capacity (flexible with ferrule) 2.5 - 16 mm² Terminal capacity (stranded) 2.5 - 16 mm² Electrical Rating

Rated operational current (Ie) - max 0 A Rated operational voltage (Ue) - max 690 V Rated uninterrupted current (Iu) 35 A

Design verification

Equipment heat dissipation, current-dependent P_{vid} 0.3 W Heat dissipation capacity P_{diss} 0 W Rated operational current

for specified heat dissipation (I_n) 35 A 10.2.2 Corrosion resistance Meets the product standard's requirements. 10.2.3.1

Verification of thermal stability of enclosures Meets the product standard's requirements. 10.2.3.2 Verification of resistance of insulating materials to normal heat Meets the product standard's requirements. 10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects Meets the product standard's requirement...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / DILM12-XEK with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.