

INDUSTRIAL COMPONENT DATA

M22-L-B 216775 Y7-216775 EATON ELECTRIC Indicator light, flush, blue

Brand: EATON - MOELLER | Manufacturer Part Number: M22-L-B



Manufacturer	EATON - MOELLER
MPN / Reference	M22-L-B
Catalog number	Y7-216775
Category	Front element for indicator light
Minimum order	1 Pcs
Document ID	EO-05AE8B86A8
Generated	2026-08-03

Product Overview

Indicator light, flush, blue

M22-L-B

Eaton Moeller® series M22 Indicator light, RMQ-Titan, Flush, Blue

Indicator light, Product range: RMQ-Titan, Single unit, Design: Flush, Color Lens: Blue, Degree of Protection: IP66, IP67, IP69K, Connection to SmartWire-DT: yes, with SWD-RMQ connections, Front dimensions: 29,7, Standards: IEC/EN 60947, VDE 0660

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **EATON - MOELLER > Auxiliary Control and Signalling Elements**

Additional Product Information

General specifications

Product Name Eaton Moeller® series M22 Indicator light

Catalog Number 216775

Model Code M22-L-B

EAN 4015082167752

Product Length/Depth 30 mm

Product Height 30 mm

Product Width 30 mm

Product Weight 0.007 kg

Certifications CE

CSA-C22.2 No. 14-05

UL File No.: E29184

CSA Class No.: 3211-03

CSA-C22.2 No. 94-91

CSA

IEC/EN 60947

VDE 0660

UL

UL Category Control No.: NKCR

CSA File No.: 012528

IEC/EN 60947-5

UL 508

Features & Functions

Bezel color Chrome

Bezel material Other

Design Flush

Fitted with: Front ring

Lens color Blue

General information

Degree of protection NEMA 4X, 13

Degree of protection (front side) IP67/IP69K

Opening diameter 22.5 mm

Overvoltage category III

Pollution degree 3

Product category RMQ-Titan

Product category RMQ-Titan

Rated impulse withstand voltage (Uimp) 4000 V AC

Size Front diameter: 29.7 mm

Type Indicator lights

Ambient conditions, mechanical

Mounting position As required

Shock resistance Mechanical, According to IEC/EN 60068-2-27

30 g, Mechanical, According to IEC/EN 60068-2-27, Sinusoidal shock 11 ms

Climatic environmental conditions

Ambient operating temperature - min -25 °C

Ambient operating temperature - max 70 °C

Climatic proofing Damp heat, constant, to IEC 60068-2-78

Damp heat, cyclic, to IEC 60068-2-30

Terminal capacities

Terminal capacity 0.5 - 1.5 mm², solid

0.5 - 1.5 mm², stranded

Electrical rating

Rated insulation voltage (Ui) 250 V

Communication

Connection to SmartWire-DT Yes

With SWD-RMQ connections

Contacts

Force for...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / M22-L-B with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.