

INDUSTRIAL COMPONENT DATA

M22-LH-A 164375 Y7-164375 EATON ELECTRIC Indicator light, raised, amber

Brand: EATON - MOELLER | Manufacturer Part Number: M22-LH-A



Manufacturer	EATON - MOELLER
MPN / Reference	M22-LH-A
Catalog number	Y7-164375
Category	Front element for indicator light
Minimum order	1 Pcs
Document ID	EO-B2EB7383B6
Generated	2026-08-01

Product Overview

Indicator light, raised, amber

M22-LH-A

Eaton Moeller® series M22 Indicator light, RMQ-Titan, Extended, conical, orange

Indicator light, Product range: RMQ-Titan, Single unit, Design: Extended, conical, Color Lens: orange, Degree of Protection: IP66, IP67, IP69K, Connection to SmartWire-DT: yes, with SWD-RMQ connections, Standards: IEC/EN 60947, VDE 0660

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Auxiliary Control and Signalling Elements

Additional Product Information

General specifications

Product Name Eaton Moeller® series M22 Indicator light Catalog Number 164375 Model Code M22-LH-A EAN

4015081608812 Product Length/Depth 30 mm Product Height 38 mm Product Width 30 mm Product Weight 0.007 kg

Certifications IEC/EN 60947

VDE 0660 Features & Functions

Bezel color Chrome Bezel material Other Design Extended, conical Lens color Orange General

Degree of protection NEMA 4X, 13 Degree of protection (front side) IP67/IP69K Opening diameter 22.5 mm Overvoltage

category III Pollution degree 3 Product category RMQ-Titan Rated impulse withstand voltage (Uimp) 4000 V AC Type

Indicator lights Ambient conditions, mechanical

Mounting position As required Shock resistance Mechanical, According to IEC/EN 60068-2-27

30 g, Mechanical, According to IEC/EN 60068-2-27, Sinusoidal shock 11 ms Climatic environmental conditions

Ambient operating temperature - min -25 °C Ambient operating temperature - max 70 °C Climatic proofing Damp heat, constant, to IEC 60068-2-78

Damp heat, cyclic, to IEC 60068-2-30 Terminal capacities

Terminal capacity 0.5 - 1.5 mm², solid

0.5 - 1.5 mm², stranded Electrical rating

Rated insulation voltage (Ui) 250 V Communication

Connection to SmartWire-DT With SWD-RMQ connections

Yes Contacts

Force for positive opening - min 0 N Design verification

Equipment heat dissipation, current-dependent P_{vid} 0 W Heat dissipation capacity P_{diss} 0 W Heat dissipation per pole, current-dependent P_{vid} 0 W Rated operational current for specified heat dissipation...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / M22-LH-A with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.