


INDUSTRIAL COMPONENT DATA

Q25LH-BL 090428 Y7-90428 EATON ELECTRIC Indicator light, raised, blue

Brand: EATON - MOELLER | Manufacturer Part Number: Q25LH-BL



Manufacturer	EATON - MOELLER
MPN / Reference	Q25LH-BL
Catalog number	Y7-90428
Category	Front element for indicator light
Minimum order	1 Pcs
Document ID	EO-D94BE35987
Generated	2026-08-04

Product Overview

Indicator light, raised, blue

Conical indicator light 16 mm 25x25 mm Blue

Eaton Moeller® series RMQ16 Indicator light, raised, blue Q25LH-BL

Indicator light, Product range: RMQ16, Single unit, Design: Conical, Description: without light elements, With base, W2x4,6d; max. 30 V, 1 W, Color Lens: Blue, Degree of Protection: IP65, Connection to SmartWire-DT: no, Front dimensions: Front dimensions 25 × 25 mm

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Auxiliary Control and Signalling Elements
--------------	---

Additional Product Information

General specifications

Product Name Eaton Moeller® series RMQ16 Indicator light Catalog Number 090428 Model Code Q25LH-BL EAN 4015080904281 Product Length/Depth 59 mm Product Height 25 mm Product Width 25 mm Product Weight 0.011 kg Certifications UL File No.: E29184

CE

CSA

UL

CSA File No.: 46552

IEC/EN 60947-5

UL 508

CSA-C22.2 No. 14-05

UL Category Control No.: NKCR

CSA Class No.: 3211-03

IEC/EN 60947 Features & Functions

Bezel color Black Bezel material Plastic Design Conical Fitted with: LED W2x4, 6d, max. 30 V, 1 W

Front ring Lens color Blue General

Degree of protection NEMA 1 Degree of protection (front side) IP65 Opening diameter 16 mm Overvoltage category III

Pollution degree 3 Product category RMQ16 Rated impulse withstand voltage (Uimp) 800 V AC Size Front dimensions: 25 ×

25 mm Terminal capacity 0.5 - 1.0 mm² Terminal size 2.8 x 0.8 mm to DIN 46247 and IEC 60760, Fast-on connectors

2.8 x 0.8 mm to DIN 46244, Blade terminal Type Indicator lights Ambient conditions, mechanical

Mounting position As required Shock resistance Mechanical, According to IEC/EN 60068-2-27

40 g, Mechanical, According to IEC/EN 60068-2-27, Sinusoidal shock 11 ms Climatic environmental conditions

Ambient operating temperature - min -25 °C Ambient operating temperature - max 60 °C Ambient operating temperature

(enclosed) - min 25 °C Ambient operating temperature (enclosed) - max 40 °C Climatic proofing Damp heat, cyclic, to IEC 60068-2-30

Damp heat, constant, to IEC 60068-2-78 Electrical rating....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / Q25LH-BL with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.