


INDUSTRIAL COMPONENT DATA

Q18LH-BL/WB 088424 Y7-88424 EATON ELECTRIC Indicator light, raised, blue, +filament lamp, 24 V

Brand: EATON - MOELLER | Manufacturer Part Number: Q18LH-BL/WB



Manufacturer	EATON - MOELLER
MPN / Reference	Q18LH-BL/WB
Catalog number	Y7-88424
Category	Front element for indicator light
Minimum order	1 Pcs
Document ID	EO-996EBD19BD
Generated	2026-08-05

Product Overview

Indicator light, raised, blue, +filament lamp, 24 V

Conical light indicator. 16 mm. 18x18 mm. Blue. With lamp

Eaton Moeller® series RMQ16 Indicator light, raised, blue, +filament lamp, 24 V Q18LH-BL/WB

Indicator light, Product range: RMQ16, Single unit, Design: Conical, Color Lens: Blue, Degree of Protection: IP65,

Connection to SmartWire-DT: no, Front dimensions: Front dimensions 18 × 18 mm

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Auxiliary Control and Signalling Elements

Additional Product Information

General specifications

Product Name Eaton Moeller® series RMQ16 Indicator light Catalog Number 088424 Model Code Q18LH-BL/WB EAN 4015080884248 Product Length/Depth 59 mm Product Height 18 mm Product Width 18 mm Product Weight 0.009 kg

Certifications CSA

IEC/EN 60947-5

UL 508

UL File No.: E29184

IEC/EN 60947

CE

UL

CSA-C22.2 No. 14-05

CSA Class No.: 3211-03

UL Category Control No.: NKCR

CSA File No.: 46552 Features & Functions

Bezel color Black Bezel material Plastic Design Conical Fitted with: Front ring Lens color Blue General

Degree of protection NEMA 1 Degree of protection (front side) IP65 Opening diameter 16 mm Overvoltage category III

Pollution degree 3 Product category RMQ16 Rated impulse withstand voltage (Uimp) 800 V AC Size Front dimensions: 18 x 18 mm Terminal capacity 0.5 - 1.0 mm² Terminal size 2.8 x 0.8 mm to DIN 46244, Blade terminal

2.8 x 0.8 mm to DIN 46247 and IEC 60760, Fast-on connectors Type Indicator lights Ambient conditions, mechanical

Mounting position As required Shock resistance Mechanical, According to IEC/EN 60068-2-27

40 g, Mechanical, According to IEC/EN 60068-2-27, Sinusoidal shock 11 ms Climatic environmental conditions

Ambient operating temperature - min -25 °C Ambient operating temperature - max 60 °C Ambient operating temperature (enclosed) - min 25 °C Ambient operating temperature (enclosed) - max 40 °C Climatic proofing Damp heat, cyclic, to IEC 60068-2-30

Damp heat, constant, to IEC 60068-2-78 Electrical rating

Rated insulation voltage (...)

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / Q18LH-BL/WB with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.