

INDUSTRIAL COMPONENT DATA

M22-LH-G 216780 Y7-216780 EATON ELECTRIC Indicator light, raised, green

Brand: EATON - MOELLER | Manufacturer Part Number: M22-LH-G



Manufacturer	EATON - MOELLER
MPN / Reference	M22-LH-G
Catalog number	Y7-216780
Category	Front element for indicator light
Minimum order	10 Pcs
Document ID	EO-E50D0489F1
Generated	2026-08-05

Product Overview

Indicator light, raised, green

M22-LH-G

Eaton Moeller® series M22 Indicator light, RMQ-Titan, Extended, conical, green

Indicator light, Product range: RMQ-Titan, Single unit, Design: Extended, conical, Color Lens: green, Degree of Protection:

IP66, IP67, IP69K, Connection to SmartWire-DT: yes, with SWD-RMQ connections, Front dimensions: 29,7, Standards:

IEC/EN 60947, VDE 0660

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **EATON - MOELLER > Auxiliary Control and Signalling Elements**

Additional Product Information

General specifications

Product Name Eaton Moeller® series M22 Indicator light Catalog Number 216780 Model Code M22-LH-G EAN

4015082167806 Product Length/Depth 30 mm Product Height 38 mm Product Width 30 mm Product Weight 0.007 kg

Certifications CSA Class No.: 3211-03

UL Category Control No.: NKCR

VDE 0660

UL File No.: E29184

CE

CSA File No.: 012528

CSA

CSA-C22.2 No. 14-05

IEC/EN 60947

IEC/EN 60947-5

UL 508

CSA-C22.2 No. 94-91

UL Features & Functions

Bezel color Chrome Bezel material Other Design Extended, conical Fitted with: Front ring Lens color Green General

Degree of protection NEMA 4X, 13 Degree of protection (front side) IP67/IP69K Opening diameter 22.5 mm Overvoltage category III Pollution degree 3 Product category RMQ-Titan Rated impulse withstand voltage (Uimp) 4000 V AC Size Front diameter: 29.7 mm Type Indicator lights Ambient conditions, mechanical

Mounting position As required Shock resistance 30 g, Mechanical, According to IEC/EN 60068-2-27, Sinusoidal shock 11 ms

Mechanical, According to IEC/EN 60068-2-27 Climatic environmental conditions

Ambient operating temperature - min -25 °C Ambient operating temperature - max 70 °C Climatic proofing Damp heat, cyclic, to IEC 60068-2-30

Damp heat, constant, to IEC 60068-2-78 Terminal capacities

Terminal capacity 0.5 - 1.5 mm², stranded

0.5 - 1.5 mm², solid Electrical rating

Rated insulation voltage (Ui) 250 V Communication

Connection to SmartWire-DT Yes

With SWD-RMQ connections Contacts

Force for positive opening - min 0...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / M22-LH-G with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.