

INDUSTRIAL COMPONENT DATA

L-R 208689 Y7-208689 EATON ELECTRIC Indicator light, red

Brand: EATON - MOELLER | Manufacturer Part Number: L-R



Manufacturer	EATON - MOELLER
MPN / Reference	L-R
Catalog number	Y7-208689
Category	Front element for indicator light
Minimum order	1 Pcs
Document ID	EO-81DE2CA76E
Generated	2026-08-02

Product Overview

Indicator light, red

L-R

Indicator light, Product range: Accessories, Design: conical, Description: can be fitted in M20/M25 knockout in base, Degree of Protection: IP66, IP67, IP69K, Bezel: titanium, Connection to SmartWire-DT: no

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Auxiliary Control and Signalling Elements

Additional Product Information

Indicator light, redIndicator light, Product range: Accessories, Design: conical, Description: can be fitted in M20/M25 knockout in base, Degree of Protection: IP66, IP67, IP69K, Bezel: titanium, Connection to SmartWire-DT: no

General specificationsProduct nameEaton Moeller® series M22 Indicator lightPart no.L-REAN4015082086893Product Length/Depth30 millimetreProduct height30 millimetreProduct width60 millimetreProduct weight0.035 kilogramCertificationsRequest filed for UL and CSAPProduct TradenameM22Product TypeIndicator lightProduct Sub TypeNoneFeatures & FunctionsBezel colorOtherBezel materialPlasticDesignConicalFitted with:Front ringLens colorRedGeneral informationDegree of protectionNEMA 4X, 13Degree of protection (front side)IP67/IP69KOpening diameter22.5 mmProduct categoryAccessoriesAmbient conditions, mechanicalShock resistance30 g, Mechanical, According to IEC/EN 60068-2-27, Sinusoidal shock 11 ms, 3 ImpactsClimatic environmental conditionsAmbient operating temperature - min-25 °CAmbient operating temperature - max70 °CCommunicationConnection to SmartWire-DTNoDesign verificationEquipment heat dissipation, current-dependent Pvid0 WHeat dissipation capacity Pdisso WHeat dissipation per pole, current-dependent Pvid0 WRated operational current for specified heat dissipation (In)0 AStatic heat dissipation, non-current-dependent Pvs0 W10.2.2 Corrosion resistanceMeets the product standard's requirements.10.2.3.1 Verification

of thermal stability of enclosuresMeets the produ...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / L-R with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.