

INDUSTRIAL COMPONENT DATA

Q18LX/WB 051741 Y7-51741 EATON ELECTRIC Indicator light, without lens, + GI 24V

Brand: EATON - MOELLER | Manufacturer Part Number: Q18LX/WB



Manufacturer	EATON - MOELLER
MPN / Reference	Q18LX/WB
Catalog number	Y7-51741
Category	Indicator light complete
Minimum order	1 Pcs
Document ID	EO-8714A1E3A4
Generated	2026-08-05

Product Overview

Indicator light, without lens, + GI 24V

Led; 16 mm; 18x18 mm; No Indicator Plate; With lamp

Eaton Moeller® series RMQ16 Indicator light, without lens, + GI 24V

Ready for use RMQ16 indicator light without lens. The pushbutton fulfils degree of protection IP65 and is approved for use world wide.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Auxiliary Control and Signalling Elements

Additional Product Information

General specifications

Product Name Eaton Moeller® series RMQ16 Indicator light Catalog Number 051741 Model Code Q18LX/WB EAN 4015080517412 Product Length/Depth 59 mm Product Height 18 mm Product Width 18 mm Product Weight 0.009 kg

Certifications IEC/EN 60947 Features & Functions

Bezel color Black Bezel material Plastic Electric connection type Flat plug-in connection Fitted with: Front ring Lens color Without hood General

Degree of protection NEMA 1

IP65 Opening diameter 16 mm Overvoltage category III Pollution degree 3 Product Category RMQ16 Rated impulse withstand voltage (Uimp) 800 V AC Terminal capacity 0.5 - 1.0 mm² Terminal size 2.8 x 0.8 mm to DIN 46244, Blade terminal

2.8 x 0.8 mm to DIN 46247 and IEC 60760, Fast-on connectors Type Indicator lights Voltage type AC/DC Ambient

conditions, mechanical

Mounting position As required Shock resistance Mechanical, According to IEC/EN 60068-2-27

40 g, Mechanical, According to IEC/EN 60068-2-27, Sinusoidal shock 11 ms Climatic environmental conditions

Ambient operating temperature - min 25 °C Ambient operating temperature - max 60 °C Ambient operating temperature (enclosed) - min 25 °C Ambient operating temperature (enclosed) - max 40 °C Electrical rating

Rated insulation voltage (Ui) 250 V Rated operational voltage (Ue) - min 0 V Rated operational voltage (Ue) - max 24 V

Rated operational voltage (Ue) at AC - max 24 V Communication

Connection to SmartWire-DT No Design verification

Equipment heat dissipation, current-dependent...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / Q18LX/WB with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.