

INDUSTRIAL COMPONENT DATA

L-Y 208691 Y7-208691 EATON ELECTRIC Indicator light, yellow

Brand: EATON - MOELLER | Manufacturer Part Number: L-Y



Manufacturer	EATON - MOELLER
MPN / Reference	L-Y
Catalog number	Y7-208691
Category	Front element for indicator light
Minimum order	1 Pcs
Document ID	EO-C0F54FDDA6
Generated	2026-08-03

Product Overview

Indicator light, yellow

L-Y

Eaton Moeller® series M22 Indicator light, yellow

Indicator light, Product range: Accessories, Design: conical, Description: can be fitted in M20/M25 knockout in base, Degree of Protection: IP66, IP67, IP69K, Bezel: titanium, Connection to SmartWire-DT: no

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Auxiliary Control and Signalling Elements

Additional Product Information

General specifications

Product Name Eaton Moeller® series M22 Indicator light Catalog Number 208691 Model Code L-Y EAN 4015082086916

Product Length/Depth 30 mm Product Height 30 mm Product Width 60 mm Product Weight 0.035 kg Certifications Request filed for UL and CSA Features & Functions

Bezel color Other Bezel material Plastic Design Conical Fitted with: Front ring Lens color Yellow General

Degree of protection NEMA 4X, 13 Degree of protection (front side) IP67/IP69K Opening diameter 22.5 mm Overvoltage category III Pollution degree 3 Product category RMQ-Titan Rated impulse withstand voltage (Uimp) 4000 V AC Size Front diameter: 29.7 mm Type Indicator lights Ambient conditions, mechanical

Mounting position As required Shock resistance Mechanical, According to IEC/EN 60068-2-27

30 g, Mechanical, According to IEC/EN 60068-2-27, Sinusoidal shock 11 ms Climatic environmental conditions

Ambient operating temperature - min -25 °C Ambient operating temperature - max 70 °C Climatic proofing Damp heat,

cyclic, to IEC 60068-2-30

Damp heat, constant, to IEC 60068-2-78 Electrical rating

Rated insulation voltage (Ui) 250 V Communication

Connection to SmartWire-DT No Contacts

Force for positive opening - min 0 N Design verification

Equipment heat dissipation, current-dependent P_{vid} 0 W Heat dissipation capacity P_{diss} 0 W Heat dissipation per pole, current-dependent P_{vid} 0 W Rated operational current for specified heat dissipation (I_n) 0 A Static heat dissipation, non-current-dependent....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / L-Y with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.