

INDUSTRIAL COMPONENT DATA

M22-L-G-LED230-BVP 132600 Y7-132600 EATON ELECTRIC

Indicator light, complete device

Brand: EATON - MOELLER | Manufacturer Part Number: M22-L-G-LED230-BVP



Manufacturer	EATON - MOELLER
MPN / Reference	M22-L-G-LED230-BVP
Catalog number	Y7-132600
Category	Front element for indicator light
Minimum order	1 Pcs
Document ID	EO-4769F94B88
Generated	2026-08-02

Product Overview

Indicator light, complete device

M22-L-G-LED230-BVP

Eaton Moeller® series M22 Indicator light, complete device M22-L-G-LED230-BVP, Blister pack for hanging Indicator light, Product range: RMQ-Titan, Description: Blister pack for hanging., Complete practical solution., Can be ordered using a single article no., Connection to SmartWire-DT: no

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Auxiliary Control and Signalling Elements

Additional Product Information

General specifications

Product Name Eaton Moeller® series M22 Indicator light Catalog Number 132600 Model Code M22-L-G-LED230-BVP EAN 4015081295357 Product Length/Depth 30 mm Product Height 210 mm Product Width 130 mm Product Weight 0.03 kg

Compliances CE Features & Functions

Bezel color Chrome Bezel material Other Lens color Green General

Degree of protection NEMA 4X, 13 Degree of protection (front side) IP67/IP69K Opening diameter 22.5 mm Overvoltage category III Pollution degree 3 Product category RMQ-Titan Rated impulse withstand voltage (Uimp) 4000 V AC Size Front diameter: 29.7 mm Type Indicator lights Ambient conditions, mechanical

Mounting position As required Climatic environmental conditions

Ambient operating temperature - min -25 °C Ambient operating temperature - max 70 °C Climatic proofing Damp heat, cyclic, to IEC 60068-2-30

Damp heat, constant, to IEC 60068-2-78 Electrical rating

Rated insulation voltage (Ui) 250 V Contacts

Force for positive opening - min 0 N Design verification

Equipment heat dissipation, current-dependent P_{vid} 0 W Heat dissipation capacity P_{diss} 0 W Heat dissipation per pole, current-dependent P_{vid} 0 W Rated operational current for specified heat dissipation (I_n) 0 A 10.2.2 Corrosion resistance

Meets the product standard's requirements. 10.2.3.1 Verification of thermal stability of enclosures Meets the product standard's requirements. 10.2.3.2 Verification of resistance of insulating materials to normal heat Meets the product standard's req...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / M22-L-G-LED230-BVP with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.