

INDUSTRIAL COMPONENT DATA

E55CBL18T110E 135842 Y7-135842 EATON ELECTRIC

Proximity switch, inductive, 1 N/C, Sn 8mm, 3L, 10-30VDC, NPN,..

Brand: EATON - MOELLER | Manufacturer Part Number: E55CBL18T110E



Manufacturer	EATON - MOELLER
MPN / Reference	E55CBL18T110E
Catalog number	Y7-135842
Category	Inductive proximity switch
Minimum order	1 Pcs
Document ID	EO-EDF6BE117F
Generated	2026-08-03

Product Overview

Proximity switch, inductive, 1 N/C, Sn=8mm, 3L, 10-30VDC, NPN, M12, insulated material, line 2m
E55CBL18T110E

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Sensors
--------------	---------------------------

Additional Product Information

Proximity switch, inductive, 1 N/C, Sn=8mm, 3L, 10-30VDC, NPN, M12, insulated material, line 2mProximity switch, Inductive Sensors, Product range: E55 Limit Switch Style Series, Connection: 3-wire, Design (outer dimensions): M18 x 1 mm, Rated operational voltage: Ue= 10 - 30 V DC, Rated switching distance: Sn= 8 mm, Type of mounting: Non-flush, Switching type: NPN, 2 m connection cable, Contacts N/C = Normally closed: 1 NC, Material: Insulated material, Degree of Protection: IP66, Standards: IEC/EN 60947-5-2Delivery program

Basic functionInductive SensorsProduct rangeE55 Limit Switch Style SeriesConnection3-wireDesign (outer dimensions)M18 x 1 mmRated operational voltage [Ue]10 - 30 V DCRated switching distance [Sn]8 mmType of mountingNon-flushSwitching typeNPNFor connection of:2 m connection cableContactsN/C = Normally closed1 NCMaterialInsulated materialDegree of ProtectionIP66Technical data

GeneralStandardsIEC/EN 60947-5-2Ambient temperature-25 - +70Mechanical shock resistance30

Shock duration 11 ms gDegree of ProtectionIP66CharacteristicsRated switching distanceRated switching distance [Sn]8 mmRepetition accuracy of Sn10 %Temperature drift of Sn10 %Switching hysteresis of Sn20 %Rated operational voltage

[Ue]10 - 30 V DC Supply frequency 50 - 60 Residual ripple of Ue 10 % Maximum load current [Ie] < 200 mA Voltage drop at Ie [Ud] 8 V Switching Frequency 500 Hz Switching state display Red LED Protective functions Short-circuit protective device Protection against polarity reversal Connect...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / E55CBL18T110E with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.