

INDUSTRIAL COMPONENT DATA

E57-30GS10-C 135971 Y7-135971 EATON ELECTRIC Proximity switch, inductive, 1N/O, Sn 10mm, 3L, 10-30VDC, NPN, ..

Brand: EATON - MOELLER | Manufacturer Part Number: E57-30GS10-C



Manufacturer	EATON - MOELLER
MPN / Reference	E57-30GS10-C
Catalog number	Y7-135971
Category	Inductive proximity switch
Minimum order	1 Pcs
Document ID	EO-3FC1BD35EF
Generated	2026-08-01

Product Overview

Proximity switch, inductive, 1N/O, Sn=10mm, 3L, 10-30VDC, NPN, M30, metal, line 2m

E57-30GS10-C

Proximity switch, E57 Global Series, 1 N/O, 3-wire, 10 - 30 V DC, M30 x 1.5 mm, Sn= 10 mm, Flush, NPN, Metal, 2 m connection cable

Proximity switch, Inductive Sensors, Product range: E57 Global Series, Connection: 3-wire, Design (outer dimensions): M30 x 1.5 mm, Rated operational voltage: Ue= 10 - 30 V DC, Rated switching distance: Sn= 10 mm, Type of mounting: Flush, Switching type: NPN, 2 m connection cable, Contacts N/O = Normally open: 1 N/O, Material: Metal, Degree of Protection: IP67, IP69K, Standards: IEC/EN 60947-5-2

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Sensors
--------------	---------------------------

Additional Product Information

Proximity switch, E57 Global Series, 1 N/O, 3-wire, 10 - 30 V DC, M30 x 1.5 mm, Sn= 10 mm, Flush, NPN, Metal, 2 m connection cable
Proximity switch, Inductive Sensors, Product range: E57 Global Series, Connection: 3-wire, Design (outer dimensions): M30 x 1.5 mm, Rated operational voltage: Ue= 10 - 30 V DC, Rated switching distance: Sn= 10 mm, Type of mounting: Flush, Switching type: NPN, 2 m connection cable, Contacts N/O = Normally open: 1 N/O, Material: Metal, Degree of Protection: IP67, IP69K, Standards: IEC/EN 60947-5-2
Delivery program

Basic function
Inductive Sensors
Product range
E57 Global Series
Connection
3-wire
Design (outer dimensions)
M30 x 1.5 mm
Rated operational voltage [Ue]
10 - 30 V DC
Rated switching distance [Sn]
10 mm
Type of mounting
Flush
Switching type
NPN
For connection of:
2 m connection cable
Contacts
N/O = Normally open
1 N/O
Material
Metal
Degree of

ProtectionIP67, IP69Technical data

GeneralStandardsIEC/EN 60947-5-2Ambient temperature-25 - +70Mechanical shock resistance30

Shock duration 11 ms gDegree of ProtectionIP67, IP69CharacteristicsRated switching distanceRated switching distance
[Sn]10 mmRepetition accuracy of Sn1 %Temperature drift of Sn10 %Switching hysteresis of Sn15 %Rated operational
voltage [Ue]10 - 30 V DCResidual ripple of Ue10 %Maximum load current [Ie]< 100 mAOperating current in the switched
state at 24 V DC [Ib]10 mAVoltage drop at Ie[Ud]1.5 VSwitching Frequency500 HzResidual current through the load in the
blocked state at 230 V AC and 24 V DC [Ir]0.0...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / E57-30GS10-C with the required quantity to info@electricaonline.com or use
electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd
Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification
requirements against the manufacturer documentation before purchase or installation.