

INDUSTRIAL COMPONENT DATA

E57LAL12A2E 135996 Y7-135996 EATON ELECTRIC Proximity switch, inductive, 1N/O, Sn 4mm, 2L, 20-250VAC, M12, m..

Brand: EATON - MOELLER | Manufacturer Part Number: E57LAL12A2E



Manufacturer	EATON - MOELLER
MPN / Reference	E57LAL12A2E
Catalog number	Y7-135996
Category	Inductive proximity switch
Minimum order	1 Pcs
Document ID	EO-07559D39B5
Generated	2026-07-31

Product Overview

Proximity switch, inductive, 1N/O, Sn=4mm, 2L, 20-250VAC, M12, metal, line 2m

E57LAL12A2E

Proximity switch, E57 Premium+ Series, 1 N/O, 2-wire, 20 - 250 V AC, M12 x 1 mm, Sn= 4 mm, Non-flush, Stainless steel, 2 m connection cable

Proximity switch, Inductive Sensors, Product range: E57 Premium+ Series, Connection: 2-wire, Design (outer dimensions): M12 x 1 mm, Rated operational voltage: $U_e = 20 - 250$ V AC, Rated switching distance: $S_n = 4$ mm, Type of mounting: Non-flush, 2 m connection cable, Contacts N/O = Normally open: 1 N/O, Material: Stainless steel, Degree of Protection: IP67, Standards: IEC/EN 60947-5-2

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Sensors
--------------	---------------------------

Additional Product Information

General specifications

Product Name Eaton Moeller® series E57 Proximity switch Catalog Number 135996 Model Code E57LAL12A2E EAN 4015081327898 Product Length/Depth 158.75 mm Product Height 50.8 mm Product Width 133.35 mm Product Weight 0.32 kg Certifications CSA

CSA Class No.: 3211-03

UL Category Control No.: NRKH, NRKH7

UL

UL 508

UL File No.: E166051

CSA-C22.2 No. 14

IEC/EN 60947-5-2

CSA File No.: 50513

CE Product specifications

Type Inductive sensor Electric connection type Cable Enclosure material finishing Other Actuation type Metallic Target Enclosure material Metal Enclosure type Cylinder, screw-thread Category (EN 954-1) B Explosion safety category for dust None Explosion safety category for gas None Safety performance level (EN ISO 13849-1) None SIL (IEC 61508) None Ambient operating temperature - max 70 °C Ambient operating temperature - min -25 °C Diameter sensor 12 mm Number of contact energized outputs with signalling function 0 Number of contacts (normally open contacts) 1 Number of outputs (protected contact energized) 0 Number of outputs (protected semiconductor) 0 Number of outputs (semiconductor with signaling function) 1 Operational current (Ib) in the switched state at 24 V DC 10 A Output current at protected output - max 0 mA Rated control supply voltage (Us) at AC, 50 Hz - max 250 V Voltage type AC Mounting method Non-flush mounting Material Stainless steel Connection type 2 m connection cable 2-wire Installation type Not flat Degree of protection IP67 NE...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / E57LAL12A2E with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.