

INDUSTRIAL COMPONENT DATA

E57LAL30T111ED 136028 EATON ELECTRIC Proximity switch, inductive, 1N/O, Sn 15mm, 3L, 6-48VDC, PNP, M30, meta..

Brand: EATON - MOELLER | Manufacturer Part Number: E57LAL30T111ED



Manufacturer	EATON - MOELLER
MPN / Reference	E57LAL30T111ED
Catalog number	136028
Category	Inductive proximity switch
Minimum order	1 Pcs
Document ID	EO-43FF620991
Generated	2026-08-04

Product Overview

Proximity switch, inductive, 1N/O, Sn=15mm, 3L, 6-48VDC, PNP, M30, metal, M12

Proximity; Inductive; 1 NO; Sn=15 mm; 3 L; 6-48 V DC; PNP; M30; Metal; M12

Proximity switch, E57 Premium+ Series, 1 N/O, 3-wire, 6 - 48 V DC, M30 x 1.5 mm, Sn= 15 mm, Non-flush, PNP, Stainless steel, Plug-in connection M12 x 1

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Sensors
--------------	---------------------------

Additional Product Information

Proximity switch, E57 Premium+ Series, 1 N/O, 3-wire, 6 - 48 V DC, M30 x 1.5 mm, Sn= 15 mm, Non-flush, PNP, Stainless steel, Plug-in connection M12 x 1

Proximity switch, Inductive Sensors, Product range: E57 Premium+ Series, Connection: 3-wire, Design (outer dimensions): M30 x 1.5 mm, Rated operational voltage: $U_e = 6 - 48$ V DC, Rated switching distance: Sn= 15 mm, Type of mounting: Non-flush, Switching type: PNP, Plug-in connection M12 x 1, Contacts N/O = Normally open: 1 N/O, Material: Stainless steel, Degree of Protection: IP67, Standards: IEC/EN 60947-5-2

Delivery program

Basic function

Inductive Sensors

Product range

E57 Premium+ Series

Connection

3-wire

Design (outer dimensions)

M30 x 1.5 mm

Rated operational voltage [U_e]

6 - 48 V DC

Rated switching distance [S_n]

15 mm

Type of mounting

Non-flush

Switching type

PNP

For connection of:

Plug-in connection M12 x 1

Contacts

N/O = Normally open

1 N/O

Material

Stainless steel

Degree of Protection

IP67

Technical data

General Standards IEC/EN 60947-5-2 Ambient temperature -25 - +70 Mechanical shock resistance 30

Shock duration 11 ms g Degree of Protection IP67 Characteristics Rated switching distance Rated switching distance [S_n] 15 mm Repetition accuracy of S_n 3 % Temperature drift of S_n 10 % Switching hysteresis of S_n 15 % Rated operational voltage

[Ue]6 - 48 V DC Operating current in the switched state at 24 V DC [Ib]10 mA Maximum load current [Ie] < 500 (6 - 30 V DC)
mA Voltage drop at Ie [Ud] 2.5 V Switching Frequency 300 Hz Min. load current [Ie] 1 mA Residual current through the...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / E57LAL30T111ED with the required quantity to info@electricaonline.com or use
electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.